



Screwless Connectors
Luminaire Connectors

LK 980-01/ 5

terminal block, 5 pole, insulating material: PA 6.6, fixing: screw, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm²



Order Info

| | |
|-----------------------------|---------------------------------|
| reference number (ref. no.) | 040015 |
| Applications | Lighting, Electrical Appliances |
| PU | 500 |
| EAN | 4028012113033 |

Type

| | |
|-------------------------|---------------------|
| type | terminal block |
| number of poles | 5 pole |
| clamping units per pole | 2 |
| colour | white |
| cross-section rating | 2.5 mm ² |

Technical Data

| | |
|-------------------------------------|--|
| voltage rating | 450 V |
| current rating | 24 A |
| insulating material | PA 6.6 |
| contact material | Spring Steel, Copper |
| flammability rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| stripping length | 8.0-9.0 mm |
| internal core cross-section max. | 1.5 / 2.5 mm ² |
| external core cross-section min. | 0.5 mm ² |
| external core cross-section max. | 2.5 mm ² |
| fixing | screw |
| internal core cross-section min. | 0.5 mm ² |
| Type of Conductor Solid External | yes |
| Type of Conductor Flexible External | yes |
| Type of Conductor Stranded External | yes |
| Type of Conductor Solid Internal | yes |
| Type of Conductor Stranded Internal | yes |
| Approbation EN60998 | LK980-01_EN60998_20070627_20101213_VDE_ENEC_40021343_v |
| Approbation UL | LK980_20010625_20110411_UL_E63492_1-18_Description_web.pdf |

Accessories

| | |
|-------------------|--------|
| WKZ 980-01 | 999041 |
| ZEL 110 | 196420 |
| ZEL 900 | 196423 |