



Screwless Connectors  
Luminaire Connectors

LK 980-01 RZ/ 3 printed "N Earth L"

terminal block, 3 pole, insulating material: PA 6.6, fixing: catch pin, printing: N Earth L, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm<sup>2</sup>



Order Info

reference number (ref. no.)	045013
Applications	Lighting, Electrical Appliances
PU	500
EAN	4028012100286

Type

type	terminal block
number of poles	3 pole
clamping units per pole	2
colour	white
cross-section rating	2.5 mm <sup>2</sup>
printing	N Earth L

Technical Data

voltage rating	450 V
current rating	24 A
insulating material	PA 6.6
contact material	Spring Steel, Copper
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
stripping length	8.0-9.0 mm
internal core cross-section max.	1.5 / 2.5 mm <sup>2</sup>
external core cross-section min.	0.5 mm <sup>2</sup>
external core cross-section max.	2.5 mm <sup>2</sup>
fixing	catch pin
internal core cross-section min.	0.5 mm <sup>2</sup>
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Stranded External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes

<b>Approbation EN60998</b>	LK980-01_EN60998_20070627_20101213_VDE_ENEC_40021343_v
<b>Approbation UL</b>	LK980_20010625_20110411_UL_E63492_1-18_Description_web.pdf

## Accessories

<b>ZEL 110</b>	196420
<b>ZEL 900</b>	196423