



Screwless Connectors
Luminaire Connectors

LK 980-01 RZ/ 5 SU printed "3 N Earth 1 2"

terminal block, 5 pole, insulating material: PA 6.6, fixing: catch pin, PE terminal: SU, printing: 3 N Earth 1 2, voltage rating: 450 V, current rating: 24 A, cross-section rating: 2.5 mm²



Order Info

| | |
|-----------------------------|---------------------------------|
| reference number (ref. no.) | 045615 |
| Applications | Lighting, Electrical Appliances |
| PU | 500 |
| EAN | 4028012113088 |

Type

| | |
|-------------------------|---------------------|
| type | terminal block |
| number of poles | 5 pole |
| clamping units per pole | 2 |
| colour | white |
| cross-section rating | 2.5 mm ² |
| printing | 3 N Earth 1 2 |

Technical Data

| | |
|-------------------------------------|---------------------------|
| voltage rating | 450 V |
| current rating | 24 A |
| insulating material | PA 6.6 |
| contact material | Spring Steel, Copper |
| flammability rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| stripping length | 8.0-9.0 mm |
| internal core cross-section max. | 1.5 / 2.5 mm ² |
| external core cross-section min. | 0.5 mm ² |
| external core cross-section max. | 2.5 mm ² |
| fixing | catch pin |
| internal core cross-section min. | 0.5 mm ² |
| Type of Conductor Solid External | yes |
| Type of Conductor Flexible External | yes |
| Type of Conductor Stranded External | yes |
| Type of Conductor Solid Internal | yes |
| Type of Conductor Stranded Internal | yes |

| | |
|----------------------------|--|
| PE terminal | SU |
| Approbation EN60998 | LK980-01 SU_SK_EN60998_20070627_20170728_VDE_40021344_web.pdf |
| Approbation UL | LK980_20010625_20110411_UL_E63492_1-18_Description_web.pdf |

Accessories

| | |
|-------------------|--------|
| WKZ 980-01 | 999041 |
| ZEL 110 | 196420 |
| ZEL 900 | 196423 |