



Screw Terminal Blocks

230/ 5 DS

terminal block, 5 pole, insulating material: PA 6, cross-section rating: 2.5 mm², pin spacing: 8.0 mm, wire protector (DS): yes, fixing: screw, voltage rating: 450 V, current rating: 24 A



Order Info

| | |
|------------------------------------|---|
| reference number (ref. no.) | 121305 |
| Applications | Lighting, Installation, Electrical Appliances |
| PU | 500 |
| EAN | 4028012105250 |

Type

| | |
|--------------------------------|---------------------|
| type | terminal block |
| number of poles | 5 pole |
| clamping units per pole | 1 |
| colour | natural |
| cross-section rating | 2.5 mm ² |
| wire protector (DS) | yes |

Technical Data

| | |
|---|---|
| voltage rating | 450 V |
| current rating | 24 A |
| insulating material | PA 6 |
| contact material | brass |
| core cross-section min. | 0.5 mm ² |
| core cross-section max. | 2.5 mm ² |
| flammability rating | V-2 |
| max. Ambient Temperature Operation | 85 °C |
| type of conductor solid | yes |
| type of conductor flexible | yes |
| type of conductor stranded | yes |
| stripping length | 5.0-5.5 mm |
| Assembly Contact Screw | 0.8x4.0 / ⚙ 0.5 Nm |
| pin spacing | 8.0 mm |
| fixing | screw |
| Approbation EN60998 | 200_230_EN60998_20012012_VDE_ENEC_40034813_web.pdf |
| Approbation UL | 230_19820924_20120103_UL_E63492_1-02_Description_web.pdf |
| Approbation CSA | Schraub_Steck_Schraubenlos_SI_Klemmen_20160429_CSA_700765 |

Accessories

| | |
|------------------|--------|
| 230 BZ/ 5 | 191205 |
| ZEL 110 | 196420 |