

**Material:**  
• Neoprene, black

**Characteristics:**  
• PG and metric thread

<b>Temperature Range</b> -25 to 100°C (-13 to 212°F)
---

Connecting thread	External diameter mm	Internal diameter mm	Thickness mm	Cat. No.	Std. Pk.
<b>PG</b>					
PG 7	17	11.3	1.2	<b>8113301</b>	100
PG 9	20	13.9	1.2	<b>8113302</b>	100
PG 11	23	17.1	1.2	<b>8113303</b>	100
PG 13.5	25	19.0	1.2	<b>8113304</b>	100
PG 16	27	21.0	1.2	<b>8113305</b>	100
PG 21	34	26.6	1.5	<b>8113306</b>	50
PG 29	45	35.2	1.5	<b>8113307</b>	50
PG 36	56	45.2	1.5	<b>8113308</b>	50
PG 42	67	52.2	1.5	<b>8113309</b>	50
PG 48	72	57.7	1.5	<b>8113310</b>	50
<b>Metric</b>					
M 12	15	10	1.2	<b>8113490</b>	100
M 16	20	13.9	1.2	<b>8113302</b>	100
M 20	24	18	1.2	<b>8113492</b>	100
M 25	30	23	1.2	<b>8113493</b>	100
M 32	40	30	1.5	<b>8113494</b>	100
M 40	48	38	1.5	<b>8113495</b>	100
M 50	58	48	1.5	<b>8113496</b>	100
M 63	75	61	1.5	<b>8113497</b>	100
M 75	90	73	1.5	<b>8113498</b>	100

