



PC card drilling dimensions(after plating)
(thickness 1.60±0.20mm)

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0000

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	E±0.07	TIN LEAD	LEAD FREE
09	30.81	24.99	16.96	16.21	10.96	D09S24A.GL00	D09S24A.GL00LF
15	39.14	33.32	25.18	24.54	19.18	D15S24A.GL00	D15S24A.GL00LF
25	53.03	47.04	39.12	38.25	33.12	D25S24A.GL00	D25S24A.GL00LF
37	69.32	63.50	55.68	54.71	49.68	D37S24A.GL00	D37S24A.GL00LF

Plating: 4 --> flash AU
Plating: 6 --> 0.76µ AU

rev	ecn no	dr	date
B	-	CJA	1999/10/18
C	LS05-001	MPE	2005/01/11
D	LS05-0056	MPE	2005/06/28
E	LS06-0097	LGO	2006/07/28
F	LS08-0172	MPE	2008/08/13
G	I10-0059	NG	2010-02-23

www.fciconnect.com		surface		tolerance std		projection		European Views	
Dr JOURBERT		ISO 1302		ISO 406 ISO 1101		mm		Scale	
Eng PESSON		ANGULAR		±0.1		A3		2	
Chr NIRMAL GEORGE		LINEAR		±0.1		ECN		I10-0059	
Appr SUDHIR VARMA		Product family		D-SUB		Spec ref		-	
1999/10/18		2010-02-23		±0.1		-		-	
1999/10/18		0.0x		±0.1		-		-	
2010-02-23		0.0x		±0.1		-		-	
2010-02-23		0.0xx		±0.1		-		-	
2010-02-23		0.0xxx		±0.1		-		-	

FCI FEMALE CONNECTOR EUROPE
 STRAIGHT STB FOR PCB 1.60mm
 C01-8646-0494
 CUSTOMER sheet 1 of 1