

WXD2020

2-Channel Solder- and Desoldering Station, 200 W (255 W)
Product no.: WXD2020N



Benefits

- › Soldering and desoldering station WXD 2, 2 channels with WXDP 120 and soldering iron WXP 120
- › Soldering- and desoldering tools with intelligent WX technology
- › Connection to external compressed air supply required
- › Energy effective: automatic stand-by mode for tools
- › Patented, ESD safe glass display. Simple and fast setting of soldering parameter.
- › Standby and auto off modes for energy savings
- › Peripheral control of WHP 1000 / WHP 3000 hot plates and Zero Smog 4V and 6V fume extraction units



Technical Data

| | |
|--|---|
| Dimensions L x W x H (mm) | 174 x 154 x 135 |
| Dimensions L x W x H (inches) | 6, 69 x 5, 94 x 5, 12 |
| Weight (approx.) in kg | 3.8 |
| Voltage | 120 V |
| Power | 200 W (255 W) |
| Channels | 2 |
| Temperature range (depends on tool) °C | 93 - 454 |
| Temperature range (depends on tool) °F | 200 - 850 |
| Temperature accuracy °C | ±9 |
| Temperature accuracy °F | ±17 |
| Temperature stability °C | ±2 |
| Temperature stability °F | ±4 |
| Equipotential bonding socket | Via 3,5 mm pawl socket on back of unit. |
| Display | 255 x 128 dots / Backlighting |
| Air consumption l/min | 35 |
| Operating pressure in bar/psi | 4,0 - 6,0 / 58 - 87 |
| Capacity l/min | --- |
| Vacuum | max. 55 kPA (8psi) |