



1PC / PE Bag

**Material:**

- Cable: USB1.1 E189529 UL2725 28#/1P+24#/2C+AEB
  - OD 4.7MM
  - Beige (IV-29#)
- P1 Connector: USB A Male Shell
  - Pin G/F
  - 4PCS Type
  - Insulator color: white
  - Shell Plate Nickel
- P2 Connector: USB A Male Shell
  - Pin G/F
  - 3PCS Type
  - Insulator color: white
  - Shell Plate Nickel
- Outer Jacket: Beige (IV-29#) PVC-40P
- 80°C 30V VW-1

**Electrical:**

- 100% short, open, miswire test
- Conduct resistance: 2Ω Max.
- Insulation resistance: 5MΩ Min.
- Dielectric test: 300V DC



|           |       |  |  |  |          |          |          |  |
|-----------|-------|--|--|--|----------|----------|----------|--|
| Scale     | 1:1   |  |  |  |          |          | Name     | Item No.<br><b>AK672-3-R</b>                                   |
| TOLERANCE |       |  |  |  | Drawn    | 01.04.12 | Chappell |  |
| X.X       | ±0.40 |  |  |  | Approved |          |          | Title<br>USB 1.1 Cable - A Male <=> B Male,<br>Beige, 3 Meters |
| X.XX      | ±0.25 |  |  |  |          |          |          |  |
| X.XXX     | ±0.15 |  |  |  |          |          |          | Drawing No.  |
| Angle     | ±3°   |  |  |  |          |          |          |  |
|           |       |  |  |  |          |          |          | <b>rev00</b>   |
|           |       |  |  |  |          |          |          | Replace  |
|           |       |  |  |  |          |          |          | Sheet  |

