

AX101943 Panels - FiberExpress Manager 1U Rack Mount Patch Panel, 19 in



For more Information
please call

1-800-Belden1



Description:

FiberExpress Manager 1U Rack Mount Patch Panel, 19 in, Empty

Usage (Overall)

Suitable Applications: FiberExpress Solutions, Backbone, Telecommunications Room, Main Distribution Room

Related Parts: FiberExpress Manager Connector Module, Splice Holder Kit, Flex Kit, Offset Bracket Kit, Cable Mgmt accessory

Physical Characteristics (Connectivity)

Capacity

Max. Capacity: 3 FiberExpress Manager Connector Module

Access

Front Connection: 1 inch Pullout

Dimensions

Dimensions:

Height (in.)	Width (in.)	Depth (in.)
1.750	19.000	12.000

Materials

Materials:

Description	Material
Panel	Steel

Color

Color: Black

Weight

Weight: 11 lbs.

Included Parts

Included Parts: labels, screws, velcro straps, cable ties, installation sheet

Packaging

Packaging: Individually packaged in a cardboard box.

Mechanical Characteristics (Connectivity)

Storage Temperature Range: -40°C To +70°C

Operating Temperature Range: -10°C To +60°C

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 01/10/2008

MII Order #39 (China RoHS): EUP 50

Safety Listing: ACA

AX101943 Panels - FiberExpress Manager 1U Rack Mount Patch Panel, 19 in

Suitability

Suitability - Indoor: Yes

Transmission Characteristics (Connectivity)

Notes (Overall)

Notes: For proper installation refer to Installation Guide PX103293 included with the product or visit our web site at <http://www.belden.com>

Product Family

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
AX101943	1 EA	16.032 LB			FXM 1U RACK MOUNT PATCHP

Revision Number: 0 Revision Date: 06-04-2009

© 2012 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.