


Product: [5100UE](#) 

Security & Sound, 2 Conductor 14 AWG, BC, CMR



## Product Description

Security & Commercial Audio Cable, Riser-CL3R-FPLR 2-14 AWG stranded bare copper conductors with polyolefin insulation, PVC jacket with ripcord

## Technical Specifications

### Product Overview

Suitable Applications:	Intercom/PA Systems, Sound/Audio Systems, Fire Alarm (For color Red only)(Dual Rated)
------------------------	---

### Physical Characteristics (Overall)

#### Conductor

Element	AWG	Stranding	Material	No. of Conductors
Conductor(s)	14	19x27	BC - Bare Copper	2

Conductor Count:	2
------------------	---

#### Insulation

Element	Material	Nominal Wall Thickness
Conductor(s)	PP - Polypropylene	0.011 in

#### Color Chart

Number	Color
1	Black
2	White

#### Outer Shield Material

Material
No Shield

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.230 in	0.017 in	Yes

### Construction and Dimensions

#### Cabling

Lay Direction	Twists
Left Hand	3 twist/ft

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
2.53 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor
22 pF/ft

## Inductance

### Nominal Inductance

0.15 µH/ft

## Current

Element	Max. Recommended Current [A]
10C Temperature Rise	Per conductor @ 25°C ambient: 8 A

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	35 lbs/1000ft
Max Recommended Pulling Tension:	95 lbs
Min Bend Radius/Minor Axis:	2.50 in

## Standards

NEC Articles:	725, 760
NEC/(UL) Specification:	CL3R, FPLR
CPR Euroclass:	Eca

## Applicable Environmental and Other Programs

Environmental Space:	Indoor - Riser
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Indoor:	Yes
-----------------------	-----

## Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Vertical Riser
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	N
Plenum Number:	6100UH

## Part Number

### Variants

Item #	Color	Putup Type	Length	UPC/EAN
5100UE 0101000	Black	Reel	1,000 ft	612825423324
5100UE 010Z1000	Black	Reel/Tuff Box	1,000 ft	612825156369
5100UE.00152	Chrome	Reel	152 m	8719605007742
5100UE.00305	Chrome	Reel	305 m	8719605007759
5100UE.00U305	Chrome	Reel	305 m	8719605007773

5100UE.00500	Chrome	Reel	500 m	8719605007766
5100UE 008500	Gray	Reel	500 ft	612825156314
5100UE 0081000	Gray	Reel	1,000 ft	612825156338
5100UE 008U1000	Gray	UnReel	1,000 ft	612825423317
5100UE 008Z1000	Gray	ReelTuff Box	1,000 ft	612825156345
5100UE 0021000	Red	Reel	1,000 ft	612825423300
5100UE 002Z1000	Red	ReelTuff Box	1,000 ft	612825156321

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

**History**

Update and Revision:	Revision Number: 0.288 Revision Date: 05-11-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.