

Product: <u>5342FE</u> ♂ Security & Sound, #18-3pr, BC, Shielded, CMR Product Description

Security & Sound Cable, Riser-CMR, 3-18 AWG stranded bare copper pairs with polyolefin insulation, Beldfoil® shield and PVC jacket with ripcord

Technical Specifications

Product Overview

Product Overview	
Suitable Applications:	Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls, Noisy Environment
Physical Characteristics (Over	rall)
Conductor	
AWG Stranding Material N	o. of Pairs
18 7x26 BC - Bare Copper 3	
Conductor Count:	6
Insulation	
Material Nominal Wall Thick	ness
PP - Polypropylene 0.007 in	
Color Chart	
Number Color	
1 Black & Red	
2 Black & White 3 Black & Green	
black a croon	
Outer Shield Material	
	Inwire Material Drainwire AWG Drainwire Construction n x D Tinned Copper 24 Solid
Outer Jacket Material	
Material Nominal Diamo	eter Nominal Wall Thickness
PVC - Polyvinyi Chioride 0.267 in	0.017 in
Electrical Characteristics	
Conductor DCR	
Nominal Conductor DCR Nominal Out	er Shield DCR
6.55 Ohm/1000ft 13.8 Ohm/100	DOft
Capacitance	
Nom. Capacitance Conductor to Condu	uctor Nom. Capacitance Conductor to Other Conductor to Shield
29 pF/ft	52.4 pF/ft
Current	
Max. Recommended Current [A]	
3.5 Amps per conductor @ 25°C A	

UL Voltage Rating 300 V RMS

300 1 100

Temperature Range

-20°C To +75°C	
	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	50 lbs/1000ft
Max Recommended Pulling Tension:	148.4 lbs
Min Bend Radius/Minor Axis:	2.7 in

Standards

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1666 Riser
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6342FE

Part Number

Variants		s	
Item #	Color	em #	UPC
5342FE 0081000	Gray	E 0081000	612825161240
Footnote:		ote:	
F 17		201	
listory		ry	
Update and Revisi	ion:	e and Revisio	

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.