



**Product:** [82760](#)

Electronic, 2 C #18 Str TC, FEP Ins, OS, PVC Jkt, CMP

[Request Sample](#)

## Product Description

Electronic Cable, 2 Conductor 18AWG (19x30) Tinned Copper, FEP Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMP

## Technical Specifications

### Product Overview

Suitable Applications:	indoor plenum applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; voice communications; panel wiring
------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### Physical Characteristics (Overall)

#### Conductor

Element	AWG	Stranding	Material	No. of Pairs
Pair(s)	18	19x30	TC - Tinned Copper	1

Conductor Count:	2
Total Number of Pairs:	1

#### Insulation

Element	Material	Nominal Wall Thickness
Pair(s)	FEP - Fluorinated Ethylene Propylene	0.0065 in

#### Color Chart

Number	Color
1	Black
	Red

#### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Alum / Poly	Beldfoil® with shorting fold	100 %	TC - Tinned Copper	20	Stranded

#### Outer Jacket Material

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness
PVC-LS - Polyvinyl Chloride (Low Smoke)	Flamarrest®	0.146 in	0.014 in

### Construction and Dimensions

#### Stranding

Lay Direction	Twists
Left Hand	6 twist/ft

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
5.5 Ohm/1000ft	7.3 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
-----------------------------------------	---------------------------------------------------------

51 pF/ft	97 pF/ft
----------	----------

#### Inductance

Nominal Inductance
0.15 µH/ft

#### Impedance

Nominal Characteristic Impedance
35 Ohm

#### Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.47 ns/ft	69 %

#### Current

Element	Max. Recommended Current [A]
10C Temperature Rise	5.4 Amps per conductor @ 25°C ambient

#### Voltage

UL Description	UL Voltage Rating
CMP	300 V

### Temperature Range

Operating Temp Range:	-20°C to +75°C
-----------------------	----------------

### Mechanical Characteristics

Bulk Cable Weight:	20 lbs/1000ft
Max Recommended Pulling Tension:	64 lbs
Min Bend Radius/Minor Axis:	1.5 in

### Standards

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP
CPR Euroclass:	Eca

### Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Flammability, LSOH, Toxicity Testing

UL Flammability:	NFPA 262
CSA Flammability:	FT6
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

### Part Number

Non-Plenum Number:	8760
--------------------	------

## Variants

Item #	Color	Putup Type	Length	UPC
82760 877U500	Natural	UnReel	500 ft	612825197737
82760 8771000	Natural	Reel	1,000 ft	612825197744
82760 877U1000	Natural	UnReel	1,000 ft	612825197720
82760 8775000	Natural	Reel	5,000 ft	612825197751

Footnote: C - CRATE REEL PUT-UP.

## History

Update and Revision: Revision Number: 0.326 Revision Date: 05-19-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.