

1	Product: <u>83002</u> ☑
	Lead Wire, #26 Str SPC, TFE Ins, AWM 1213 105C TYPE E
	Request Sample
Product Description	

High Temp Plastic Lead Wire, 26AWG (7x34) Silver Plated Copper, TFE Insulation, AWM 1213 105C TYPE E MIL-W-16878/4 600V 200C

# **Technical Specifications**

## Physical Characteristics (Overall)

	Conductor		
AWG Stranding	Material	No. of Conductors	
26 7x34	7x34 SC - Silvered Copper		
Conductor Count:		1	
nsulation			
Material	Nominal	Diameter Nominal	
PTFE - Polytetrafluo	roethylene 0.039 in	0.01 in	
Electrical Char	acteristics		
Conductor DCR			
Nominal Conducto	r DCR		
37.5 Ohm/1000ft			
Current			
Eleme	ent Ma	ax. Recommended C	
Mil-Std-975M Table	3.16 (single wire) 2.	5 amps	
Voltage			
-	tage Rating [V]		
Mil-W-16878/4 600	V		
Tamana tama D			
Temperature R			
Non-UL Temp Ratin	g:	200°C	
UL Temp Rating:	200.	105°C -70°C To +200°C	
Operating Temp Pag			
Operating Temp Rai	ige.		
Operating Temp Ran			
		2 lbs/1000ft	
Mechanical Ch			
Mechanical Ch Bulk Cable Weight: Standards		2 lbs/1000ft	
Mechanical Ch Bulk Cable Weight: Standards UL AWM Style:	aracteristics	2 lbs/1000ft 1213	
Mechanical Ch Bulk Cable Weight: Standards UL AWM Style: Military Specification	aracteristics	2 lbs/1000ft 1213 NEMA HP3, MIL-W	
Mechanical Ch Bulk Cable Weight: Standards UL AWM Style: Military Specification	aracteristics	2 lbs/1000ft 1213	
Mechanical Ch Bulk Cable Weight: Standards UL AWM Style: Military Specification	aracteristics	2 lbs/1000ft 1213 NEMA HP3, MIL-W	

EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

### Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
UL voltage rating:	600 V RMS
Plenum/Non-Plenum	

#### Plenum (Y/N):

#### **Part Number**

#### Variants

Item #	Color	Putup Type	Length	UPC
83002 010100	Black	Reel	100 ft	612825354864
83002 0101000	Black	Reel	1,000 ft	612825353850
83002 006100	Blue, Light	Reel	100 ft	612825353874
83002 0061000	Blue, Light	Reel	1,000 ft	612825399223
83002 001100	Brown	Reel	100 ft	
83002 0011000	Brown	Reel	1,000 ft	612825353911
83002 008100	Gray	Reel	100 ft	
83002 0081000	Gray	Reel	1,000 ft	612825399230
83002 005100	Green, Dark	Reel	100 ft	
83002 0051000	Green, Dark	Reel	1,000 ft	
83002 003100	Orange	Reel	100 ft	612825353898
83002 0031000	Orange	Reel	1,000 ft	
83002 002100	Red	Reel	100 ft	612825354895
83002 0021000	Red	Reel	1,000 ft	612825353904
83002 007100	Violet	Reel	100 ft	
83002 0071000	Violet	Reel	1,000 ft	
83002 009100	White	Reel	100 ft	
83002 0091000	White	Reel	1,000 ft	612825353867
83002 004100	Yellow	Reel	100 ft	
83002 0041000	Yellow	Reel	1,000 ft	612825399216
Footnote:			E - MAY C	ONTAIN MORE
Footnote:				ING ADDERS FO

No

#### History

Update and Revision: Revision Number: 0.286 Revision Date: 04-28-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.