



**Product:** 9462 □

Electronic, 2 C #22 Str TC, PVC Ins, OS, PVC Jkt, CMG

### **Product Description**

Electronic, 2 Conductor 22AWG (7x30) Tinned Copper, PVC Insulation, Overall Beldfoil® Shield, PVC Outer Jacket, CMG

### **Technical Specifications**

### **Product Overview**

Suitable Applications: low voltage analog signals (4-20ma, 0-10v, ...); low voltage digital control (24v, ...); line level audio; computer communication; panel wiring

### **Physical Characteristics (Overall)**

#### Conductor

Element	AWG	Stranding	Material	No. of Pairs
Pair(s)	22	7x30	TC - Tinned Copper	1
Conductor Count: 2				
Total Number of Pairs: 1				

### Insulation

Element	Material	Nominal Wall Thickness
Pair(s)	PVC - Polyvinyl Chloride	0.01.35 in

#### **Color Chart**

Number	Color
1	Black & Red

### Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Alum / Poly	Beldfoil® (Z-Fold®)	100 %	TC - Tinned Copper	22	7x30

### **Outer Jacket Material**

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.186 in	0.035 in

### **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR 16 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Condu	uctor Nom. Capacitance Conductor to Other Conductor to Shield
50 pF/ft	90 pF/ft

#### Inductance

Nominal Inductance 0.19 µH/ft

### Impedance

# Nominal Characteristic Impedance 36 Ohm

### Current

## Max. Recommended Current [A]

3 Amps per conductor @ 25°C A

### Voltage

## UL Voltage Rating

300 V RMS

### **Temperature Range**

UL Temp Rating:	80°C (UL AWM Style 2464)
Operating Temp Range:	-30°C To +80°C

### **Mechanical Characteristics**

Bulk Cable Weight:	19 lbs/1000ft
Max Recommended Pulling Tension:	27 lbs
Min Bend Radius/Minor Axis:	2 in

### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMG
CEC/C(UL) Specification:	CMG
UL AWM Style:	UL Style 2464 (300 V 80°C)
CPR Euroclass:	Eca

### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
MII Order #39 (China RoHS):	Yes

### Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS

### Plenum/Non-Plenum

Plenum (Y/N):	No

### **Part Number**

### Variants

Item #	Color	UPC
9462 060100	Chrome	612825253464
9462 0601000	Chrome	612825253471
9462 060500	Chrome	612825253488
9462 0605000	Chrome	612825253495
9462 060U1000	Chrome	612825253440
9462 060U500	Chrome	612825253457

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Z - FINAL PUT-UP MAY VARY (= OR -) 10% FOR SPOOLS OR REELS AND (+ OR -) 5% FOR UNREEL CARTONS FROM LENGTH SHOWN.

### **History**

Update and Revision:

Revision Number: 0.304 Revision Date: 05-11-2020

### © 2020 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.