



**Product:** [9916](#)

Lead Wire, #16 Str TC, PVC Ins, AWM 1007 AWM 1569

[Request Sample](#)

**Product Description**

Low Temp Plastic Lead Wire, 16AWG (26x30) Tinned Copper, PVC Insulation, AWM 1007 AWM 1569 CSA TYPE TR-64 TRSR-64

**Technical Specifications**

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	No. of Conductors
16	26x30	TC - Tinned Copper	1

Conductor Count: 1

**Insulation**

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.092 in	0.016 in	0.015 in

**Construction and Dimensions**

**Cabling**

Twists
6 twist/ft

**Electrical Characteristics**

**Voltage**

Non-UL Voltage Rating	UL Voltage Rating
300 V	300 V

**Temperature Range**

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C

**Mechanical Characteristics**

Bulk Cable Weight:	11.5 lbs/1000ft
--------------------	-----------------

**Standards**

UL Rating:	300V RMS, 80°C and 300V, 105°C
UL AWM Style:	UL Style 1007 (300 V 80°C), UL Style 1569 (300 V 105°C)
CSA Rating:	300V RMS, 105°C
CSA AWM Specification:	TRSR-64
CSA Type:	TRSR-64
Military Specification:	N/A

**Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
--------------------------------	-----

EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color	Putup Type	Length	UPC
9916 010100	Black	Reel	100 ft	612825261988
9916 0101000	Black	Reel	1,000 ft	612825261995
9916 0105000	Black	Reel	5,000 ft	612825262008
9916 013100	Blue, Dark	Reel	100 ft	612825262015
9916 0131000	Blue, Dark	Reel	1,000 ft	612825262022
9916 001100	Brown	Reel	100 ft	612825261797
9916 0011000	Brown	Reel	1,000 ft	612825261803
9916 0081000	Gray	Reel	1,000 ft	612825261933
9916 005100	Green, Dark	Reel	100 ft	612825261896
9916 0051000	Green, Dark	Reel	1,000 ft	612825261902
9916 0031000	Orange	Reel	1,000 ft	612825261858
9916 002100	Red	Reel	100 ft	612825261827
9916 0021000	Red	Reel	1,000 ft	612825261834
9916 0025000	Red	Reel	5,000 ft	612825261841
9916 007100	Violet	Reel	100 ft	612825261919
9916 0071000	Violet	Reel	1,000 ft	612825261926
9916 009100	White	Reel	100 ft	612825261940
9916 0091000	White	Reel	1,000 ft	612825261957
9916 0095000	White	Reel	5,000 ft	612825261964
9916 004100	Yellow	Reel	100 ft	612825261865
9916 0041000	Yellow	Reel	1,000 ft	612825261872

Footnote:	P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.
-----------	---

## History

Update and Revision:	Revision Number: 0.288 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.