

CHEMTRONICS®

Technical Data Sheet

TDS # 2284

Max-Kleen™ Xtreme™

The extra-strength, nonflammable heavy-duty degreaser

PRODUCT DESCRIPTION

Max-Kleen™ Xtreme™ is ideal for removal of all types of soils including tar and grease from tools, clutches, bearings and housings. It is a non-corrosive and nonconductive cleaner. Max-Kleen™ Xtreme™ will evaporate quickly without leaving a residue behind.

- Quickly removes all types of tough soils including oxidized oil and grease
- Dielectric strength of 18 kV
- Contains n-propyl bromide
- Nonflammable, no flash point
- Penetrates to clean hard to reach areas
- Non-corrosive and non-conductive
- Leaves no residue
- Ozone safe
- Test on plastics

TYPICAL APPLICATIONS

Max-Kleen™ Xtreme™ can be used for all repair, maintenance, and manufacturing applications including:

- Removes grease, oil, lubricants, wax and tar
- Cleans contacts, relays and switches, circuit breakers and fuse blocks
- All repair and maintenance cleaning including: controls, conveyors and gear drives
- Cleans electric motors and gasoline engines
- Removes tough soils from gears and pulleys
- Use for maintenance of air compressors

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

Boiling Point	156° F (Initial)
Evaporation Rate (butyl acetate=1)	>1
Flash Point (TCC)	None
Specific Gravity	1.35
Vapor Pressure @68°F	112 mmHg
Appearance	Clear, colorless liquid
Odor	Mild
Solubility in Water	Negligible
Dielectric Breakdown (ASTM D-877)	18 kV
Kauri-Butanol (KB) Number	125
Shelflife	5 years

COMPATIBILITY

Max-Kleen™ Xtreme™ is compatible with most metals. As with any solvent, compatibility with plastics should be determined on a non-critical area prior to use. Materials such as polystyrene and ABS are not compatible with the cleaning solvent in Max-Kleen™ Xtreme™.

Material**Compatibility**

ABS	Non-Compatible
Buna-N	Fair
EPDM	Fair
Graphite	Excellent
HDPE	Excellent
LDPE	Good
Lexan™	Fair
Neoprene	Fair
Noryl®	Poor
Nylon™ 66	Excellent
Cross-Linked PE	Excellent
Polypropylene	Excellent
Polystyrene	Non-Compatible
PVC	Excellent
Silicone Rubber	Poor
Teflon™	Excellent
Viton™	Fair

AVAILABILITY

ES2284	19 oz aerosol
ES184	1 gal. Liquid
ES5584	55 gal. drum

TECHNICAL & APPLICATION ASSISTANCE

ITW Chemtronics® provides a technical hotline to answer your technical and application related questions. The toll free number is:

1-800-TECH-401.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. ITW CHEMTRONICS® does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

Chemtronics® is a registered trademark of ITW Chemtronics. All rights reserved. Max-Kleen™, Xtreme™ and Controlwipes™ are trademarks of ITW Chemtronics. All rights reserved.

All other trademarks herein are trademarks or registered trademarks of their respective owners.

MANUFACTURED BY:

ITW CHEMTRONICS®

8125 COBB CENTER DRIVE

KENNESAW, GA 30152

1-770-424-4888

REV A (02/06)

DISTRIBUTED BY:**USAGE INSTRUCTIONS**

Read MSDS carefully prior to use.

Spray 4-6 inches from surface to clean. Wash parts from top to bottom, allowing the liquid to flush away dirt and dissolved grease. For precise application use attached extension tube.

Dip applications - Allow the soiled article to soak in Max-Kleen™ Xtreme™ for 5 - 10 minutes, then remove and loosen any remaining soils with a Controlwipes™ Wipe.

For wipe applications, wet a Controlwipes™ Wipe with Max-Kleen™ Xtreme™ and wipe away soils.

SAFETY & ENVIRONMENTAL DATA

SAFETY & ENVIRONMENTAL DATA			
CFC	0.0%	VOC	100%
HCFC-225	0.0%	HFC	0.0%
HCFC-141b	0.0%	nPB	100%