

Thermometer with Ethernet interface and relays

code: H0530



Ambient temperature Ethernet sensor with two relay outputs.

Sensor H0530 is designed for online monitoring of temperature. Three binary inputs to detection of two-states signals are the advantage. Other devices are controlled by two relay outputs.

Technical data

| | |
|--|---|
| TEMPERATURE SENSOR | |
| Measuring range | -30 to +80 °C |
| Accuracy | ±0.4 °C |
| Resolution | 0.1 °C |
| RELAY OUTPUTS | |
| Quantity | 2 |
| Maximal voltage | 50 V |
| Maximal current | 2 A |
| Maximal power | 60 VA |
| BINARY INPUTS | |
| Quantity | 3 |
| Signal for binary input | dry contact, open collector or two-state voltage signal. Inputs are not galvanically isolated. |
| Minimum pulse duration on binary input | 500 ms |
| Voltage across open contact | < 3,3 V |
| Low voltage level | 0 to +0,5 V |
| High voltage level | +3,0 to +30 V |
| GENERAL TECHNICAL DATA | |
| Operating temperature | -30 to +80 °C |
| Channels | internal temperature sensor |
| Acoustic alarm | from built-in beeper - switchable |
| Output | Ethernet |
| Measuring interval | 2 s |
| Available temperature units | degrees Celsius, degrees Fahrenheit |
| Communication protocol | WWW, ModbusTCP, SNMPv1, SOAP, XML |
| Alarm protocols | E-mail (SMTP authentication is supported), SNMP Trap, Syslog |
| Power | 9-30 Vdc |
| Protection class | IP40 |
| Dimensions | 136 x 191 x 45 mm; stem length 53 mm |

| | |
|----------|---------------|
| Weight | approx. 340 g |
| Warranty | 3 years |