



NOTES:

1. METALSHELLS: COPPER ALLOY;
min. 315µm TIN over 40-80µm NICKEL
2. INSULATOR: TPE
3. CLAMPS: STAINLESS STEEL
4. SCREW: STAINLESS STEEL
5. CONNECTOR IS PART MARKED: PART NO. CONEC ABC

RoHS compliant

No. of pos.	A _{-0,76}	B ^{+0,25}	C	Part-No. Bulk package	Part-No. Single package
9	31,19	16,46	25,00 ^{+0,12} _{-0,13}	165X16669X	165X16669XE
15	39,52	24,79	33,30 ^{+0,15} _{-0,1}	165X16679X	165X16679XE
25	53,42	38,50	47,04 ± 0,13	165X16689X	165X16689XE
37	69,70	54,96	63,50 ± 0,13	165X16699X	165X16699XE
50	67,31	52,55	61,10 ^{+0,14} _{-0,11}	165X16709X	165X16709XE

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

				tolerance		scale:	2:1
						dim. in mm	material:
				date	name	title: HOOD 9 - 50pos. FOR PLUG CONNECTOR water resistant, shielded for EMI/RFI	
				drawn 30.06.2011	Henneboel		
				appd. 01.07.2011	Fischer		
				norm			
				d-old		dwg no:	DIN-A4
a	Original					16K1A2842	sh: 1
rev.	description	date	name			part no:	SEE TABLE