


## 15555.2

### PRC LW 110...125V AC/DC

### PRC LW 110...125V AC/DC



Plug-Relay-Compact (PRC) socket base PRC with screw connection and residual current suppression for long cables, Mounting type: Mounting rail TS 35, 1 CO contact, Input voltage: 110 to 125 VAC/DC

#### Business data

Product description	Relay socket base with screw connection
Packaging unit	10
Quantity unit	PC
Weight per piece (not including packaging)	29.9
Weight per piece (including packaging)	31.89
Unit of weight	G
Customs number	85369010
Country of origin	EEC

## 15555.2

PRC LW 110...125V AC/DC

PRC LW 110...125V AC/DC

### Technical Data

---

#### Dimensions

---

Length	87.3 mm
Width	6.2 mm
Height TS 35 / 7.5 with BA	79.9 mm

#### Ratings

---

Rated voltage Un	110-125 VAC/DC
Overvoltage category	III
Contamination degree	3

#### Connection data

---

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.2 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	2.5 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Stripping length	10 mm
Torque	0.5 Nm

**15555.2**

**PRC LW 110...125V AC/DC**

**PRC LW 110...125V AC/DC**

## Technical Data

---

### Output data

---

Switching voltage / switching voltage max.	250 / 400 VAC
--	---------------

Contact configuration	1 CO contact
-----------------------	--------------

### Materials

---

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	70 °C
---------------------------	-------

### Further technical data

---

Protection	IP20
------------	------

Status display	✓
----------------	---

AC residual current suppression	✓
---------------------------------	---

**15555.2**

**PRC LW 110...125V AC/DC**

**PRC LW 110...125V AC/DC**

## Approvals

---

## Standards and regulations

---

CE compliant

✓

15555.2

PRC LW 110...125V AC/DC

PRC LW 110...125V AC/DC

## Media

---

