


16004.2 CP VH 40-2 CP VH 40-2



Overvoltage arrester type 2, Consisting of base element and protective plug with high-performance varistor, remote signalling contact, Mounting type: Mounting rail TS 35, 2-channel, Rated voltage: 230 VAC

Business data

Product description	Overvoltage arresters
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	199.8
Weight per piece (including packaging)	215.9
Unit of weight	G
Customs number	85354000
Country of origin	FR

© CONTA-CLIP Verbindungstechnik GmbH | Otto-Hahn-Str. 7 | D-33161 Hövelhof
Fon +49 (0) 52 57.98 33-0 | Fax +49 (0) 52 57.98 33-33 | E-Mail info@conta-clip.de | conta-clip.de

Creation date 08.06.2020 11:03:23
Subject to technical modifications

16004.2

CP VH 40-2

CP VH 40-2

Technical Data

Dimensions

Length	100.6 mm
Width	36 mm
Height	70 mm
Installation dimensions acc. to DIN 43880	2 Te

Ratings

Rated voltage Un	230 / 400
Rated discharge surge current In (8/20) μ s	40 kA
Rated frequency min.	50 Hz
Rated frequency max.	60 Hz
Short-circuit resistance Ip	25 kA

Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	4 mm ²
Wire cross-section single-core (rigid), max.	25 mm ²
Wire cross-section stranded, min.	4 mm ²
Wire cross-section stranded, max.	25 mm ²

16004.2

CP VH 40-2

CP VH 40-2

Technical Data

Connection data

Wire cross-section stranded with wire-end ferrules, min.	25 mm ²
--	--------------------

Wire cross-section stranded with wire-end ferrules, max.	4 mm ²
--	-------------------

Output data

Switching current, max. at 30 V DC	2 A
------------------------------------	-----

Switching current, max. at 250 V AC	0,5 A
-------------------------------------	-------

Remote signalling	Potential-free CO contact
-------------------	---------------------------

Remote signalling: Wire cross-section single-core (rigid), max.	1,5 mm ²
---	---------------------

Materials

Insulation housing	Thermoplastic
--------------------	---------------

Flammability class UL 94	V-0
--------------------------	-----

Working temperature, min.	-40 °C
---------------------------	--------

Working temperature, max.	85 °C
---------------------------	-------

16004.2

CP VH 40-2

CP VH 40-2

Technical Data

Further technical data

Protection class	IP20
Response time t_A	<25 ns
Max. continuous voltage	280 V
Discharge current I_{max} (8/20) μ s, max.	80 kA
Protection level U_p	<1,25 kV
Residual voltage U_{res} (5 kA)	<0,5 kV
Operating current I_c	<1 mA
Follow-on current I_f	None
Follow-on current extinguishing capacity I_{fi}	Infinite
TOV voltage U_t (L-N)	340 V / 5 s
Series fuse, max.	125 A
Malfunction display	Mechanical, red
Type of mains network	TN (2+0)

16004.2

CP VH 40-2

CP VH 40-2

Approvals

Standards and regulations

DIN EN 61643-11 (Germany)

Arrester type 2

EN 61643-11 (Europe)

Low voltage SPD - Class II test

IEC 61643-1 (International)

Low voltage SPD - Class II test

UL1449 ed.2 (USA)

Low voltage TVSS

16004.2

CP VH 40-2

CP VH 40-2

Media

