

2092.0

TS 15 perforated

TS 15 GL



DIN rail, slotted, Width: 15 mm, Height: 5.5 mm, Material: Steel, Colour: natural

Business data

Product description	DIN rail
Packaging unit	40
Quantity unit	M
Weight per piece (not including packaging)	150
Weight per piece (including packaging)	150
Unit of weight	G
Customs number	72166110
Country of origin	EEC

2092.0

TS 15 perforated

TS 15 GL

Technical Data

Dimensions

Length	2000 mm
Hole length	12 mm
Width	15 mm
Hole width	4.2
Height	5.5 mm
Hole spacing (mid-point to mid-point)	20 mm
Thickness	1 mm
Shape of hole	Slotted hole
Slotted hole	✓
Slotted	✓

Ratings

Max. short-circuit current	1.2 kA
Max. allowed thermal rated current with PEN function	Schutzleiter-Sammelschienen aus Stahl sind für PEN-Funktion nicht zulässig! A
Short-circuit resistance I _p	10 kA

Materials

Material	Steel
----------	-------

2092.0

TS 15 perforated

TS 15 GL

Technical Data

Materials

Surface

Galvanized, thick-film passivated

2092.0

TS 15 perforated

TS 15 GL

Approvals

Standards and regulations

Standards / specifications

DIN EN 60715

VDE approval

VDE approval

Acc. DIN VDE 0611-3

2092.0

TS 15 perforated

TS 15 GL

Media

