



All information contained herein applies only to the above listed part number. Other versions of this part number with electrical or mechanical variations are available. Contact CUI Inc. for further assistance. 9615 SW Allen Blvd., Ste. 103, Beaverton OR 97005
 800-275-4899 • 503-643-4899 • Fax: 503-643-6129 • www.cui.com

Medical Grade Switching Power Supply



Input

Input voltage range	90~264VAC
Rated input	100~240VAC
Input current	0.5A(rms) @ 115VAC 0.25A(rms) @ 230VAC
Input frequency	47~63Hz
Rated frequency	50~60Hz
Inrush current	max. 40A @ 230V cold start

Output

Output voltage	6VDC \pm 6%
Rated current	2.0A
Ripple & noise	50mV P-P max
Leakage current	0.25mA max @ 264VAC input

General

Hi-Pot test	3.0KVAC/1S - primary to secondary / primary to case
Insulation resistance	50M Ω Min. - primary to secondary / primary to case 500VDC
Protection	short circuit protection

Environmental

Operating temperature	0~40°C @ max. load
Storage temperature	-40~85°C
Humidity	5%~95% non-condensing

Mechanical

Dimensions	74.5x46.5x29.0mm (2.93x1.83x1.14")
Weight	approx. 130g

DC Output Cord/Plug

Output cord	20AWG, UL1185, white, 1.2meters \pm 10cm
Output plug	5.5x2.1x12mm



All information contained herein applies only to the above listed part number. Other versions of this part number with electrical or mechanical variations are available. Contact CUI Inc. for further assistance. 9615 SW Allen Blvd., Ste. 103, Beaverton OR 97005
 800-275-4899 • 503-643-4899 • Fax: 503-643-6129 • www.cui.com

Safety Standards

CSA for the US	UL2601-1 Std. 2 nd edition
CSA for Canada	CAN/CSA C22.2 No. 601.1-M90
	CSA 601.1 Supplement 1: 1994
	CSA 601.1 Amendment 2: 1998
NEMKO	EN60601-1 (1990) 2 nd ed. + A1 (1993) + A2 (1995) + A12 (1993) + Corrigenda (1994): Medical Electrical Equipment- Part 1: General Requirements for safety.
	EMC Standard: EN60601-1-2:93
CE Mark	EN60601-1 (1990) + A1 (1993) + A2 (1995) + A13 (1996) + Corrigenda (July 1994). EMC Standard: EN60601-1-2:93.
	Complies with Medical Device Directive 93/42/EEC
CB Scheme	EN60601-1 (1990) + A1 (1993) + A2 (1995) + A12 (1993) + A13 (1996) + Corrigenda (July 1994), IEC 60601-1 (2 nd ed. 1998) +

Case Dimensions

