



ELECTRICAL SPECIFICATIONS

| | |
|---------------------------|-------------|
| FREQUENCY RANGE (GHz): | 3.50 - 7.00 |
| ISOLATION (dB): | 17 MIN |
| INSERTION LOSS (dB): | 0.50 MAX |
| VSWR: | 1.35 MAX |
| POWER: AVG (PORT 1 TO 2): | 20W |
| REFLECTIVE POWER (TERM): | 2W |
| PEAK: | 40W |

MECHANICAL SPECIFICATIONS

| | |
|------------------------|----------------------------------------|
| CONNECTORS: | SMA-FEMALE, STAINLESS STEEL, PASSIVATE |
| CONTACT PINS: | BERYLLIUM COPPER, GOLD PLATE |
| OPERATING TEMPERATURE: | 0° to +50°C |
| WEIGHT (APPROX): | 1.20 OUNCES |

| | | | |
|--------------------------------------------------------|-----------------------------------|-----------------------------------------------------------------------|--|
| DIMENSIONS IN INCHES, UNLESS OTHERWISE SPECIFIED | | Dilom MICROWAVE INC. <small>Fresno, California, USA</small> | |
| TOLERANCE XX±0.03 XXX±0.010 | TITLE 3.50 - 7.00 GHz Isolator | | |
| SCALE 4:1 | MODEL NO D313570 | REV | |