



CIRCUIT 5 POSITION

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NOS. FOR REFERENCE ONLY.
 4. CONTACT RATINGS: 25mA @24VDC.
 5. CONTACT MATERIAL:
CONTACTS: BRASS w/Gold Plate
TERMINALS: BRASS w/GOLD Plate
 6. PACKAGED: DISPENSING TUBES
WITH ALL POLES IN THE "OFF" POSITION.
 7. TAPE SEAL FOR FLUX WASH.
 8. ▲ DESIGNATE MAJOR:

RECOMMENDED P.C.B. LAYOUT

E-SWITCH®

| | | | | | | | | | |
|--|--|---------|--|-------------------------|--|--------|--|---------|--|
| REV. A | | 12277 | | RELEASED FOR PRODUCTION | | 7/1/02 | | CJB | |
| REV. A | | ECN No. | | DESCRIPTION | | DATE | | CHKD | |
| THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED | | | | | | | | | |
| TITLE | | SCALE | | DATE | | DATE | | DR | |
| KAJ05 TG GT | | 2:1 | | 7/1/02 | | 7/1/02 | | CJB | |
| LDW PROFILE W/TAPE SEAL | | | | | | | | DWG | |
| | | | | | | | | W825325 | |
| | | | | | | | | REV | |
| | | | | | | | | A | |