



- NOTES:
1. ALL DIMENSIONS IN MM [INCH]
 2. GENERAL TOLERANCE: X.X=± 0.4
X.XX=± 0.25
 3. RATING: 12VDC, 50mA MAX.
 4. CONTACT RESISTANCE: 500mΩ MAX.
 5. INSULATION RESISTANCE: 100VDC, 100MΩ MIN.
 6. TRAVEL: 0.25 mm
 - ▲ 7. OPERATING FORCE: 160 +75/-30gf
 8. OPERATING TEMPERATURE: -20°C TO 70°C
 9. OPERATING LIFE: 30,000 CYCLES.
 10. PACKAGING: TAPE & REEL, 3000 PIECES PER REEL
 11. ▲ DENOTES CRITICAL PARAMETER
 12. 2002/95/EC (ROHS) COMPLIANT

LED Specifications	Units	WHITE	BLUE
Forward Current	mA	30	15
Forward Voltage	V	3.5-4.0	3.5-3.8
Luminous Intensity@20mA	mcd	180	45



A	18249	RELEASE FOR PRODUCTION	9/19/08	BLR
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE TL3200AF160WBQ				
SCALE	DATE	DR	DWG	REV
8:1	9/19/2008	BLR	B200107	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED