



## Plug-and-Play 100W Constant Voltage LED Driver


The SLV 100 -SI series is a UL Class 2 100 Watt LED driver series with constant voltage output. 12 V auxiliary cable output options are available for connection with IoT sensors or active cooling devices. This series can be easily upgraded with dimming options by combining with any of GRE Alpha's dimming module accessories for information, please visit (<https://grealpha.com/products/led-dimming-modules/>).

# SLV 100-SI

## Constant Voltage LED Drivers



### Model Selection Key



### Features

- UL LED Driver, enabling drastically reduced approval times and agency approval costs.
- Wide Input Voltage: 90-305 VAC
- Extremely Low operating temperature - 40°C to 60°C
- SCP, OCP, OTP, OVP
- UL Class P
- UL Type HL
- 3 Years Warranty

### Applications

- Architectural Lighting
- Effect & Contour Lighting
- Office General Illumination
- Warehouses
- Street Lighting
- Signage
- Strip Lighting
- Swimming Pools/Fountain lighting
- Horticultural Lighting

Model Number	Input Voltage Range (V <sub>AC</sub> )	Channel(s) Output	Preset Vout (V <sub>DC</sub> )	Load Range (per Channel) (A)		Max Output Power (per Channel) (W)	Total Output Power (W)
				min	max		
SLV100-112V-SI	100-277	1	12	0	8.33	100	100
SLV100-112V-SI(A)	100-277	1	12	0	8.33	100	100
SLV100-124V-SI	100-277	1	24	0	4.20	100	100
SLV100-124V-SI(A)	100-277	1	24	0	4.20	100	100
SLV100-148V-SI	100-277	1	48	0	2.10	100	100
SLV100-148V-SI(A)	100-277	1	48	0	2.10	100	100

SI = Waterproof standard aluminum housing

(A) - With 12V 300mA Auxiliary Output

## Input Specification

Voltage Range	Frequency Range	Max Inrush Current	Power Factor	THD
100-277 VAC	50-60 Hz	35A@120 VAC input, 25°C, cold start-up	0.9 min @100-277 VAC, Full load	<15% @ full load

## Output Specification

Max Power	100 W	Transient Response	8 mS, full load to 40% load, 100 VAC Input
Line Regulation	+/- 1% Max	Short Circuit Protection	Hiccup-Mode, Auto-Recovery upon removal of short circuit condition.
Efficiency	Up to 92%	Constant Voltage (CV) Mode Load Regulation	+/- 5% Max
Noise/Ripple	<2% of Rated Output Voltage*	Over Current Protection	Hiccup-Mode
Hold-up Time	0.5 mS @ full load, 100VAC input	Start-up Time	0.5 sec. Typical@ start-up to full load, 120VAC input
Auxiliary Output	12V 300mA		



\* All noise measurements made at the output terminals, connected to a 20MHz low pass filter.

## Environmental Specifications

MTBF	Cooling	Operating Temp	Storage Temp	Relative Humidity
100,000 hours (Full load @ 25°C Ambient, Based on MIL-217F)	Convection	-40°C to 60°C (Full load)	-40°C to 85°C	5% to 95 %

## Compliance / Safety

EMI/RFI:	CISPR-22 Class B FCC part 15 Class B EN 55015
Safety Standards:	UL1012/1585, UL8750,UL879, UL Class 2,Class P, Type HL UL 48,cUL, CE, UL #: E342485 EN 61347-2-13, CCC, PSE
Weatherability:	EN60529 IP 65
Surge Immunity	Line - Line: 2.5kV Line - Earth: 4kV

INPUT		SJTW 18AWG
OUTPUT (Standard)		12V: SJTW 16AWG 24V: SJTW 18AWG 48V: SJTW 18AWG
OUTPUT (Auxiliary)		UL2464 rated, 22AWG

## Mechanical


### Material:

NEMA 3 Design with aluminum extruded enclosure, with IP65 waterproof, fully potted PCB.


### Dimensions:

195.4(L)\*60.7(W)\*37.1(H)mm

## Mechanical Diagrams



Packing Information:  
 0.832kg/pc; 6 pcs/carton;  
 Weight: 6.8kgs/carton  
 230(L)\*185(W)\*210(H) mm



Packing Information:  
 0.838kg/pc; 6 pcs/carton;  
 Weight: 6.85kgs/carton  
 230(L)\*185(W)\*210(H) mm

Information furnished is believed to be accurate and reliable. However, GRE Alpha assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of GRE Alpha. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.

The GRE Alpha logo is a registered trademark of GRE Alpha Electronics Ltd.  
 All other names are the property of their respective owners

Copyright © 2019 GRE Alpha. All rights reserved. Reproduction in whole or in part without permission is prohibited.

SLV100-201902

Preliminary datasheet for reference only