

Specification Sheet

Part Number: 148-90036



HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 2-Port, (PC), Yellow, 150/pkg

Article Number 148-90036

Type HCPM-2

Color Clear (CL) Yellow (YE)

Features & Benefits

- Spring technology for safe, secure and reliable connections.
- Smaller footprint fits in tight spaces.
- Low insertion force makes installation of solid or stranded copper wire fast and easy.
- Color coded for easy identification of size.
- Each port accepts multiple wire diameters for flexible applications.
- Accepts 12–22 AWG solid wire and 14–22 AWG stranded wire.

Quantity Per box

Product Description	HelaCon Plus Mini Wire Connectors replace traditional twist-on wire connectors. They provide faster, easier and more reliable connection and distribution of cable and conductors in electrical installation applications. Mini connectors have a compact footprint and can be applied tool-free using convenient, push-in simplicity. Internal spring technology is approved for solid and stranded wires.
Short Description	HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 2-Port, (PC), Yellow, 150/pkg
Global Part Name	HCPM-2-PC-CL/YE
Length L (Imperial)	0.65
Length L (Metric)	16.5
Width W (Imperial)	0.42
Width W (Metric)	10.8
Height H (Imperial)	0.30
Height H (Metric)	7.70
Depth D (imperial)	0.65
Depth D (metric)	16.5
Material	Polycarbonate (PC)

Material Shortcut	PC
Flammability	UL 94 V0
Halogen free	Yes
Operating Temperature (Metric)	-22°F to +185°F (-30°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	SGS Fimko Ltd EN 60998-2-2:2004 cULus UL ANSI/UL 486-A NEMKO AS EN 60998-2-2:2004 VDE DIN EN 60998-2-2:2005-03 SGS Fimko Ltd EN 60998-2-2:201 Intertek Semko EN 60998-2-2:2004 UL ANSI/UL 486-C UL ANSI/UL 486-B CE 2006/65/EC ENEC
UL Listed (US and Canada)	Yes
UL Listed (US	Yes
Package Quantity(Imperial)	150
Package Quantity (Metric)	150
Customs Number	8536695050
Content Unit(BMEcat)	pcs.

