## **HellermannTyton**

## **Specification Sheet**

Part Number: 166-90790



HelaGuard NM Ultra IP68 Fitting, 45-Degree Elbow, .50" NPT Thread, .38" Dia., PA66, Black, 1/pkg

Article Number 166-90790

**Type** HGU038-45-0500

Color Black (BK)

Features & Benefits

- Integrated Sealing Technology includes conduit insert seal and high-performance face-sealing washer for ease of use and durability.
- True one-piece component for fast Snap-On application reduces installation time and costs by eliminating the need to thread fittings onto conduits. All-around "teeth" attach firmly to corrugated conduit and deliver a high extraction force. Elbow features a smooth bore to ease cable installation. PA66 nylon material has high resistance to salts, oils, weak acids, and solvents. Integrated design delivers IP66 + IP67 + IP68 + IP69 ingress protection against moisture and dirt.

Quantity Per

pack

Product Description	Elbow Snap-On style Metric or NPT threaded nylon fittings provide a true one-piece component solution; seals and locknuts are included. Durable nylon materials deliver high chemical resistance against salts, oils, weak acids, and solvents. Designed for easy removal with a small scrowdriver LIL-Listed fittings deliver IR66 + IR67 + IR68 +
	a small screwdriver. UL-Listed fittings deliver IP66 + IP67 + IP68 + IP69 ingress protection.

Short Description	HelaGuard NM Ultra IP68 Fitting, 45-Degree Elbow, .50" NP1	
	Thread, .38" Dia., PA66, Black, 1/pkg	

Global Part Name	HGU038-45-0500-PA66-BK

Length L (Metric)	58.0

Variant	45° Elbow	

Outside Diameter OD(Imperial)	1.14	

	Outside Diameter OD(metric)	29.0
--	-----------------------------	------

Nominal [	Diameter (Imperial)	0.38
Nominal [	Diameter (Imperial)	0.38

<b>Nominal Diameter</b>	(Metric)	16
=	,,	. •

Material Shortcut	PA66
Material Shortcut	PA66

 Flammability
 Self-Extinguishing

 Halogen free
 Yes

 Operating Temperature (Metric)
 -58°F to +275°F (-50°C to +135°C)

 ROHS Complaint
 Yes

 Package Quantity(Imperial)
 1

Package Quantity (Metric) 1

Customs Number 3926909988

© 2020 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions