

Specification Sheet

Part Number: 166-90849



HelaGuard Non-Metallic IP68 Fitting, Straight, M20 Thread, 0.50" Dia, PA66, Black, 10/pkg

Article Number 166-90849

Type HGL050-S-M20

Color Black (BK)

Features & Benefits

- External Metric thread provides a secure connection.
- Snap-on construction reduces installation time and costs by eliminating the need to thread fittings onto conduits.
- All-around "teeth" attach firmly to conduit and deliver a high extraction force.
- Durable nylon material has high resistance to salts, oils, weak acids and solvents.
- IP68 fitting has additional conduit seal for increased protection against wind, dirt, and water.

Quantity Per pack

| | |
|---------------------------------------|--|
| Product Description | HelaGuard Non-Metallic Straight Swivel Flange fitting features a snap-on design that provides a quick, secure connection. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Designed for easy removal with a small screwdriver. IP68 ingress protection rated fittings. |
| Short Description | HelaGuard Non-Metallic IP68 Fitting, Straight, M20 Thread, 0.50" Dia, PA66, Black, 10/pkg |
| Global Part Name | HGL050-S-M20-PA66-BK |
| Length L (Imperial) | 1.73 |
| Length L (Metric) | 44 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Operating Temperature (Metric) | -58°F to +275°F (-50°C to +135°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 10 |
| Package Quantity (Metric) | 10 |
| Customs Number | 3926909988 |

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)