

Specification Sheet

Part Number: 181-00322



High Density Slotted Wall Wiring Duct, 2.5" x 3", Non- Adhesive, PVC, Black, 120ft/Carton

Article Number 181-00322

Type SLHD2.5X3

Color Black (BK)

Features & Benefits

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size and are offered every 2 inches to accommodate compact designs and ease installation.
- Optional covers snap on and off easily, and are provided with a non-slip lining that insures the covers remain in place during vibration.

Quantity Per carton

| | |
|---|--|
| Product Description | HellermannTyton Pro-Duct High-Density, Slotted-Wall Wiring Duct features narrow fingers equaling a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated. |
| Short Description | High Density Slotted Wall Wiring Duct, 2.5" x 3", Non- Adhesive, PVC, Black, 120ft/Carton |
| Global Part Name | SLHD2.5X3-PVC-BK |
| Technical Description | Non- Adhesive |
| Length L (Imperial) | 6.0 |
| Length L (Metric) | 1.83 |
| Width W (Imperial) | 2.5 |
| Width W (Metric) | 63.5 |
| Height H (Imperial) | 3.07 |
| Height H (Metric) | 77.9 |
| Mounting Hole Centers (Imperial) | 2.0 |
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |

| | |
|--|--|
| Flammability | Self-Extinguishing |
| Halogen free | No |
| Operating Temperature (Metric) | +122°F (+50°C) |
| Reach Complaint(Article 33) | No |
| ROHS Complaint | Yes |
| Certification/Specification WEB | EN 50085-1:2005 + A1:2013 CSA UL EN 50085-2-3_1A |
| UL Recognized (US) | Yes |
| Package Quantity(Imperial) | 120 |
| Package Quantity (Metric) | 36.58 |
| Customs Number | 3925900000 |