

## Specification Sheet

Part Number: 596-00240

RATED AC OPERATING CURRENT	
MAX RATED AC OPERATING CURRENT	
RATED AC OPERATING VOLTAGE	
MAX RATED AC OPERATING VOLTAGE	
RATED SHORT CIRCUIT CURRENT	
MAXIMUM SYSTEM VOLTAGE	

Solar Label, Printable, DC BACKUP SYSTEM, 4.0" x 2.0", PET, Red, 50/roll

**Article Number** 596-00240

**Type** ACRATING

**Color** Red (RD)

**Features & Benefits**

- Made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- High abrasion and scuff resistance for high-performance labeling.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Quantity Per** roll

**Product Description**

Designed with cross-laminated UV stable materials, these variable print solar installation labels are designed to accept printing from any standard thermal transfer printer using a resin-based ink ribbon for the best durability. Print your voltage information directly on the label and then laminate with an optional clear acrylic laminate material for added protection. These labels can be used to print disconnecting means and breaker series directly on the labels for a more professional result and a smoother inspection process.

<b>Short Description</b>	Solar Label, Printable, DC BACKUP SYSTEM, 4.0" x 2.0", PET, Red, 50/roll
<b>Global Part Name</b>	ACRATING-840/281-RD
<b>Technical Description</b>	Printable Solar Label, AC Ratings (Operating, Max Operating and Max System Current; Operating and Max Voltage) 4.0" X 2.0", Red
<b>Width W (Imperial)</b>	4.0
<b>Width W (Metric)</b>	101.6
<b>Thickness T (Imperial)</b>	0.0025
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	2.0
<b>Height H (Metric)</b>	50.8
<b>Material</b>	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
<b>Material Shortcut</b>	840/281
<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	Yes

<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature (Metric)</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	NEC2017 UL 969 NEC2020 NEC2014 IFC 2012 CSA 66956
<b>Warranty (US)</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3919102055
<b>Content Unit(BMEcat)</b>	pcs.
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	0.521
<b>Weight (Imperial)</b>	1.14

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)