


## Specification Sheet

Part Number: 596-00249



Solar Circuit Marker, CAUTION: SOLAR CIRCUIT, 4" x 2", V, Red, 25/pkg

<b>Article Number</b>	596-00249
<b>Type</b>	CSCSNAP4R
<b>Color</b>	Red (RD)

### Features & Benefits

- Pre-printed solar labels are made using high performance UV stable materials and adhesives for long outdoor life.
- Designed to meet NEC and IFC standards for PV installation labeling, the pre-printed Solar labels come printed with the most common legends required by the AHJ (Authority Having Jurisdiction) used on large utility and scaled projects to ensure code compliance during inspection.
- Labels are UV stable and made with special high bond adhesives to stick to both powder coat painted surfaces and baked enamel surfaces found on most disconnect switches and breaker boxes.
- The printed inks meet the fire safety standards of the IFC (International Fire Code) and also meet the requirements of UL969 for high reflectivity and durability.

<b>Quantity Per</b>	pack
<b>Product Description</b>	These photovoltaic caution and power source markers are preprinted, non-adhesive, coiled markers that can be opened and snapped over cables for long-term, reflective, permanent identification. Made of a UV stable vinyl, the coiled markers come 25 per bag and will fit on all standard PV cables or electrical metallic tubing (EMT) conduits.
<b>Short Description</b>	Solar Circuit Marker, CAUTION: SOLAR CIRCUIT, 4" x 2", V, Red, 25/pkg
<b>Global Part Name</b>	CSCSNAP4R-V-RD
<b>Technical Description</b>	Pre-Printed Solar Marker, Reflective, Non-adhesive, Coiled, "CAUTION: SOLAR CIRCUIT", 4" X 2", Red
<b>Width W (Imperial)</b>	4.0
<b>Width W (Metric)</b>	101.6
<b>Height H (Imperial)</b>	3.0
<b>Height H (Metric)</b>	76.2
<b>Material</b>	Vinyl
<b>Material Shortcut</b>	V
<b>Halogen free</b>	No

<b>Operating Temperature (Metric)</b>	-18°F to +200°F (-29°C to +93°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	NEC2017 NEC2011 IFC 2012 NEC2014 UL 969
<b>Package Quantity(Imperial)</b>	25
<b>Package Quantity (Metric)</b>	25
<b>Customs Number</b>	3919905060
<b>Weight (Metric)</b>	0.074
<b>Weight (Imperial)</b>	0.16