

Specification Sheet

Part Number: 596-00621



Pre-Printed Header Label, WARNING, 6.0" x 4.0", PET, Orange, 250/roll

Article Number

596-00621

Type

4X6WARNING

Color

Orange (OG)

Features & Benefits

- Pre-printed solar labels are made with UV-stable inks and materials for durability and weather resistance.
- Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
- High abrasion and scuff resistance for high performance labeling.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Quantity Per

roll

Product Description	HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
Short Description	Pre-Printed Header Label, WARNING, 6.0" x 4.0", PET, Orange, 250/roll
Global Part Name	4X6WARNING-336/926-OG
Technical Description	Pre-Printed Header Label, WARNING, 4" X 6", Orange
Width W (Imperial)	6.0
Width W (Metric)	152.4
Thickness T (Metric)	64.0
Height H (Imperial)	4.0
Height H (Metric)	101.6
Width of Liner (Metric)	106.6
Width of Liner (imperial)	4.2

Material	Type 336/926, Polyester, UV-stabilized, clear polyester laminate (336/926)
Material Shortcut	336/926
Adhesive	Acrylic
Halogen free	Yes
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +302°F (-40°C to +150°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	250
Package Quantity (Metric)	250
Customs Number	3919102055
Labels per Column	1
Labels per Row	1
Weight (Metric)	0.521

