

## Specification Sheet

Part Number: 596-00654

PHOTOVOLTAIC SYSTEM DC DISCONNECT	
OPERATING CURRENT:	<input type="text"/>
OPERATING VOLTAGE:	<input type="text"/>
MAXIMUM SYSTEM VOLTAGE:	<input type="text"/>
SHORT CIRCUIT CURRENT:	<input type="text"/>

Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 50/roll

**Article Number**

596-00654

**Type**

DCRATING-1

**Color**

Red (RD)

**Features & Benefits**

- Made with UV-stable inks and materials for durability and weather resistance.
- Reflective properties to meet applicable NEC code requirements for reflective identification.
- Supplied with an aggressive adhesive to ensure long life.
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Quantity Per**

roll

<b>Product Description</b>	Designed in a one-across landscape format to fit into the compact TT130SMC thermal transfer printer, these labels allow for code-compliant marking of variable information including disconnecting means, breaker series and voltage data. Made with cross-laminated UV stable materials, labels are ideal for use in solar installation applications. Use with the TT130SMC or any HellermannTyton thermal transfer printer.
<b>Short Description</b>	Solar Label, Printable, DC Rating, 3.75" x 2.0", PET, Red, 50/roll
<b>Global Part Name</b>	DCRATING-1-840/281-RD
<b>Technical Description</b>	Printable Solar Label, DC RATING LABEL, 2.0" X 3.75", Red
<b>Width W (Imperial)</b>	2.0
<b>Width W (Metric)</b>	50.8
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	3.75
<b>Height H (Metric)</b>	95.25
<b>Material</b>	Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281)
<b>Material Shortcut</b>	840/281
<b>Adhesive</b>	Acrylic

<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature (Metric)</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL 969
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	50
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	0.521
<b>Weight (Imperial)</b>	1.14

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)