

Specification Sheet

Part Number: RTT750HR.NX900



Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg

Article Number	115-00001
Type	SpeedyTie (RTT750HR)
Color	Red (RD) Yellow (YE)
Features & Benefits	<ul style="list-style-type: none">• The heavy duty Speedy tie features a specially designed head and patented trigger to allow for repeated use in temporary bundling applications.• Additional design feature on the head allows excess strap to be tucked away after installation.
Quantity Per	bag
Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes or temporary bundling are necessary. The head design guarantees high tensile strength even after repeated use.

Short Description	Releasable Cable Tie, 29.6" Long, 200 lb Tensile Strength, PA66, Yellow, 5/pkg
Global Part Name	SpeedyTie (RTT750HR)-PA66-RD/YE
Minimum Tensile Strength (Imperial)	200.0
Minimum Tensile Strength (Metric)	888.0
Length L (Imperial)	29.6
Length L (Metric)	752.0
Identification Plate Position	none
Releasable Closure	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.51
Width W (Metric)	13.0
Bundle Diameter Min (Imperial)	1.6
Bundle Diameter Min (Metric)	40.0
Bundle Diameter Max (Imperial)	8.3

Bundle Diameter Max (Metric)	210.0
Thickness T (Imperial)	0.075
Thickness T (Metric)	1.9
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +185°F (-40°C to +85°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	5
Package Quantity (Metric)	5
Customs Number	3926909988
Content Unit(BMEcat)	pcs.
Weight (Metric)	23.2

© 2020 HellermannTyton. All Rights Reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)