

Specification Sheet

Part Number: T250M0X2



Heavy Duty Cable Tie, 22" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg

Article Number 111-25001

Type T250M

Color Black (BK)

Features & Benefits

- Engineered and manufactured for maximum performance and quality.
- Made from 100% high-quality plastic to ensure efficient recycling.
- Inside serration for a strong grip onto bundles.
- Easy application either manually or with a tensioning tool.

Quantity Per bag

| | |
|--|--|
| Product Description | These cable ties offer a high minimum tensile strength and have a buckle feature which allows the end of the cable tie to be tucked away if necessary. The buckle also snaps into HellermannTyton lashing tie mounts (LTM.) T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Short Description | Heavy Duty Cable Tie, 22" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg |
| Global Part Name | T250M-PA66-BK |
| Minimum Tensile Strength (Imperial) | 250.0 |
| Minimum Tensile Strength (Metric) | 1115.0 |
| Length L (Imperial) | 22.0 |
| Length L (Metric) | 565.3 |
| Identification Plate Position | none |
| Releasable Closure | No |
| Tie Closure | plastic pawl |
| Variant | Inside Serrated |
| Width W (Imperial) | 0.49 |
| Width W (Metric) | 12.4 |

| | |
|--|--|
| Bundle Diameter Min (Imperial) | 0.47 |
| Bundle Diameter Min (Metric) | 12.0 |
| Bundle Diameter Max (Imperial) | 5.9 |
| Bundle Diameter Max (Metric) | 150.0 |
| Thickness T (Imperial) | 0.07 |
| Thickness T (Metric) | 1.9 |
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Halogen free | Yes |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| Reach Complaint(Article 33) | Yes |
| ROHS Complaint | Yes |
| Certification/Specification WEB | UL ANSI/UL 1565 UL ANSI/UL 746B UL ANSI/UL 62275 |
| UL Recognized (US) | Yes |

UL Recognized (US and Canada) Yes

Package Quantity(Imperial) 25

Package Quantity (Metric) 25

Customs Number 3926909988

Content Unit(BMEcat) pcs.

Weight (Metric) 12