

Jun.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTE 1)	STORAGE TEMPERATURE RANGE	-10°C TO +60°C	
	VOLTAGE	100 V AC	APPLICABLE CONNECTOR	DF19#-*P-1H (56)	
	CURRENT	0.5 A			
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="radio"/>	<input type="radio"/>	
MARKING	CONFIRMED VISUALLY.		<input type="radio"/>	<input type="radio"/>	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARKS			APPROVED	TY.OMA	06.02.09
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.			CHECKED	HK.UMEHARA	06.02.09
Unless otherwise specified, refer to JIS C 5402.			DESIGNED	IO.DENPOUYA	06.01.28
			DRAWN	AH.MIYAZAKI	06.01.28
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-311700-01	
	SPECIFICATION SHEET		PART NO.	DF19G-*S-1F-GND (05)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL685-	1/