

May.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
Rating	Operating Temperature Range	-25°C to +60°C	Storage Temperature Range	-25°C to +60°C
	Voltage	—	Operating Humidity Range	—
	Curent	—	Applicable Cable	—
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
General Examination	Visually and by measuring instrument.	According to drawing.	X	X
Marking	Confirmed visually.		X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
0				
REMARK		APPROVED	NM. NISHIMATSU	17. 02. 07
Unless otherwise specified, refer to IEC 60512.		CHECKED	NM. NISHIMATSU	17. 02. 07
		DESIGNED	MO. SHIMOYAMA	17. 02. 07
		DRAWN	JY. IGA	17. 02. 07
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC-120682-06-00	
HRS	SPECIFICATION SHEET	PART NO.	TM11APA1-88P (06)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL222-2783-4-06	△ 1/1