



May.1.2020 Copyright 2020 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C $\triangle 1$	STORAGE TEMPERATURE RANGE	-25 °C TO 60 °C $\triangle 1$
	VOLTAGE	AC 125 V	CURRENT	0.5 A
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="radio"/>	<input type="radio"/>
MARKING	CONFIRMED VISUALLY.		<input type="radio"/>	<input type="radio"/>
ELECTRIC CHARACTERISTICS				
CONTACT RESISTANCE	100 mA DC (OR 1000 Hz AC). MEASUREMENT POINTS SHALL BE AS FOLLOWS.  (ONE EXAMPLE CONNECTOR CONFIGURATION IS SHOWN.)	230 mΩ MAX.	<input type="radio"/>	<input type="radio"/>
INSULATION RESISTANCE	100 V DC.	100 MΩ MIN.	<input type="radio"/>	<input type="radio"/>
VOLTAGE PROOF	500 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	<input type="radio"/>	<input type="radio"/>
MECHANICAL CHARACTERISTICS				
MECHANICAL OPERATION	200 TIMES INSERTIONS AND EXTRACTIONS.	1) CONTACT RESISTANCE: 250 mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="radio"/>	-
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, - m/s ² AT 2 h, FOR 3 DIRECTIONS.	1) NO ELECTRICAL DISCONTINUITY OF 5μs. 2) CONTACT RESISTANCE: 250 mΩ MAX. 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="radio"/>	-
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		<input type="radio"/>	-
ENVIRONMENTAL CHARACTERISTICS				
DAMP HEAT, CYCLIC	EXPOSED AT +40 °C, 90 TO 95 %, 500 h.	1) CONTACT RESISTANCE: 250 mΩ MAX. 2) INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY) 10 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="radio"/>	-
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55±3 → 5 TO 35 → 85±2 → 5 TO 35 °C TIME 30 TO 35 → 5 MAX → 30 TO 35 → 5 min MAX UNDER 5 CYCLES.	1) CONTACT RESISTANCE: 250 mΩ MAX. 2) INSULATION RESISTANCE: 100 MΩ MIN. 3) NO DAMAGE, CRACK AND LOOSENESS OF PART	<input type="radio"/>	-
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	1) CONTACT RESISTANCE: 250 mΩ MAX. 2) NO HEAVY CORROSION.	<input type="radio"/>	-
RESISTANCE TO SOLDERING IRON HEAT	SOLDERING IRON TEMPERATURE, 350 ± 10°C SOLDERING TEMPERATURE 4 s MAX.			
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
2	DIS-E-00002217	TS. ITO	TU. TANIGUCHI	20190425
REMARK		APPROVED	HO. MIWA	20060117
		CHECKED	YH. ENAMI	20060117
		DESIGNED	TU. TANIGUCHI	20060117
Unless otherwise specified, refer to JIS C 5402.		DRAWN	MT. ITANO	20060117
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-122138-01	
HRS	SPECIFICATION SHEET	PART NO.	TM18R-T0-88 (50)	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL222-2883-9-50	$\triangle 1$ 1/2

REFLOW CONDITION



TEMPERATURE RANGE	TIME
150 TO 180	60 SEC
200 MIN	55 SEC
220MIN	40 SEC
230MIN	30 SEC
235 MIN	20 SEC
240	MOMENT

Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-122138-01	
SPECIFICATION SHEET HIROSE ELECTRIC CO., LTD.		PART NO.		TM18R-T0-88 (50)	
		CODE NO.		CL222-2883-9-50	△ 2/2