




HOME	ABOUT US	INDUSTRIES	PRODUCTS & APPLICATIONS		NEWS & EVENTS	CONTACT & SUPPORT		EXTRANETS
Speed, Position & Current	Thermal	Pressure, Force & Flow	Relays	Switches & Equipment Health	Potentiometers & Resistors	Safety Products	Vehicle Controls & Monitoring	Test & Measurement

## Honeywell Sensing and Control

Where to buy 

 [Interactive Catalog Home](#)





 [Product Family Information](#)

 [Specification Search](#)

 [Search Help](#)



*Representative photograph, actual product appearance may vary.*

-  [Dimensions](#)
-  [Schematic](#)
-  [Performance Charts](#)
-  [Specifications](#)

[Click here for a print friendly version of this datasheet.](#)

## SD5410-001

### SD Series Silicon PhotoDarlington, TO-46 Metal, Glass Lensed Can Package

#### Features

- TO-46 metal can package
- Choice of flat window or lensed package
- 90 ° or 12 ° (nominal) acceptance angle option
- Wide operating temperature range [-55 °C to 125 °C]
- Wide sensitivity ranges
- Mechanically and spectrally matched to SE3450/5450, SE3455/5455 and SE3470/5470 infrared emitting diodes

#### Description

The SD3410/5410 series consists of an NPN silicon photodarlington mounted in a TO-46 metal can package. The SD3410 has flat window cans providing a wide acceptance angle, while the SD5410 has glass lensed cans providing a narrow acceptance angle. The TO-46 packages are ideally suited for operation in hostile environments.

Product Specifications	
<b>Product Type</b>	IR Component
<b>Angular Response (Degree)</b>	12
<b>Light Current Minimum</b>	2.0 mA
<b>Package Style</b>	T0-46, Dome Lensed
<b>Package Components</b>	Metal
<b>Rise and Fall Time</b>	75 $\mu$ s
<b>Power Dissipation</b>	150 mW
<b>Operating Temperature Range</b>	-55 °C to 125 °C [-67 °F to 257 °F]
<b>Dark Current</b>	250 nA
<b>Collector-Emitter Breakdown Voltage</b>	15 V
<b>Emitter-Collector Breakdown Voltage</b>	5 V
<b>Collector-Emitter Saturation Voltage</b>	1.1 V
<b>Comment</b>	The radiation source is a tungsten lamp operating at a color temperature of 2870°K.
<b>Availability</b>	Global
<b>Product Name</b>	Photodarlington

*Due to regional agency approval requirements, some products may not be available in your area.  
Please contact your regional Honeywell office regarding your product of choice.*