


Actuator shown in pos. 1

P.C. MOUNTING



CONTACT ARRANGEMENT

code for x	function	actuator in position 1	actuator opposite to pos. 1
D	On-On	1-2	2-3

code for x	function	actuator in position 1	actuator in center	actuator opposite to pos. 1
E	On-Off-On	1-2	open	2-3

Specifications:

- Contact rating: max. 0.4VA, max. 48V AC or DC, max. 50mA
min.: 1µA, 20mV AC or DC
- Contact resistance: 50mOhm max.
- Insulation resistance: 500MOhm min. at 250V DC
- Dielectric strength: 500V, 50Hz for the duration of 1 minute
- Operating temperature: -20°C to +85°C
- Electrical life: min. 40 000 cycles
- Soldering conditions: wave-soldering: 260 +/-5°C, 5 +/-1sec.
- Protection: IP67
- Material: Actuator: PBT, yellow
Housing: brass, nickel plated
Case: PBT, meets (UL94V-0), washable
Contact / terminals: phosphor bronze, gold plated over nickel barrier
Cap: silicone rubber



Tolerances: 0.00: ±0.25mm 0.0: ±0.40mm		Date	Name	<h1>ASE 1 x</h1>
		03/14	dr	
			knitter-switch	<h1>30 30 60</h1>
Modifications		Date	Name	Page 1/1