





# ePanel-PM

## Mobile Flatpanel SBC



powered by  
Intel® Pentium® M



- Intel® Celeron® M and Pentium® M CPU (600 MHz up to 1.4 GHz)
- Low power consumption
- Prepared for wireless LAN/Internet, Bluetooth connections etc. via PC-CARD-Slot or Mini-PCI (e.g. for DVB-T)
- Low profile form factor
- Ideal suitable for warehouse management, indoor visual units, Rear-seat-video, ...
- Shortest time to market by highest integration of interfaces and features

## Product Overview


Do you need an ultraflat single board computer to be mounted directly behind a flat panel? **ePanel-PM** is a complete SBC with a very low height based on low power Intel® Celeron® M or Pentium® M.

A wide range of software is available for this proven x86 platform. In addition to the very low power consumption, the high number of interfaces is remarkable. So, systems can be designed within a very short period and built with minor additional engineering efforts.

## Technical Information

<b>Processor</b>	Intel® Celeron® M and Pentium® M 600 MHz - 1.4 GHz
<b>Chipset</b>	GM 852 or GME 855/ICH4
<b>Memory</b>	1 x DDR-SODIMM SDRAM, 200pin, 2.5V, up to 1GByte
<b>Graphics</b>	Intel® Extreme Graphics with shared memory Flatpanel Interface: TTL and LVDS on board NTSC/Pal video input Touch screen: 4/5/8 wire supported matrix controller
<b>Ethernet</b>	100 MBit Ethernet
<b>USB</b>	3 x USB 2.0

<b>Dimensions</b>	140 x 180 mm
<b>Battery</b>	Smart-Battery backup supported
<b>Power Supply</b>	Wide range DC (8 to 28 V)
<b>I/O Features</b>	Flexible I/O adapter solution: 1 x VGA / Sound connector 1 x Floppy Connector 1 x secondary IDE 1 x secondary port connector 1 x Compact Flash socket PC-CARD interface on Board Mini PCI for Bluetooth, Wireless LAN, CAN, DVB-T, etc.



## Ordering Information

Article	Part.-No.	Description
ePanel-CM 600 (800) MHz	22242	ePanel-CM 600 MHz with Intel® Celeron® M ULV CPU and GM852 Chipset
ePanel-CM 1 GHz	22243	ePanel-CM 1 GHz with Intel® Celeron® M ULV CPU and GME855 Chipset
ePanel-PM 1.4 GHz	22244	ePanel-PM 1.4 GHz with Intel® Pentium® M LV CPU and GME855 Chipset
I/O Adapter	22223	I/O Adapter for standard interfaces (e.g. USB, VGA, RS232 etc.)
ePanel-PM Starterkit	60900	Including I/O-adapter, video-adapter, power supply, 512 MB CF-Card, 256 MB DDR-RAM and cables for: power supply, I2C-Bus, touch-panel and matrix keyboard, HD-Adapter. Reset-Button, Power-Button.
DDR-SDRAM-SODIMM 256 MB	97007-2560-00-0	DDR-SDRAM SODIMM PC2700 memory module with 256 MB
DDR-SDRAM-SODIMM 512MB	97007-5120-00-0	DDR-SDRAM SODIMM PC2700 memory module with 512 MB
DDR-SDRAM-SODIMM 1GB	97007-1024-00-0	DDR-SDRAM SODIMM PC2700 memory module with 1 GB

## Corporate Offices

**Europe, Middle East & Africa**  
Oskar-von-Miller-Str. 1  
85386 Eching/Munich  
Germany  
Tel.: +49 (0)8165/ 77 777  
Fax: +49 (0)8165/ 77 219  
sales@kontron.com

**North America**  
14118 Stowe Drive  
Poway, CA 92064-7147  
USA  
Tel.: +1 888 294 4558  
Fax: +1 858 677 0898  
sales@us.kontron.com

**Asia Pacific**  
17 Building,Block #1,ABP.  
188 Southern West 4th Ring Road  
Beijing 100070,P.R.China  
Tel.: + 86 10 63751188  
Fax: + 86 10 83682438  
kcn@kontron.cn

**Kontron Embedded Modules GmbH**  
Flatpanel Solutions  
Hamburger Straße 181  
22083 Hamburg - Germany  
Tel.: +49(40)200090-0  
Fax: +49(40)200090-10  
sales-graphic@kontron.com