



ANXAFT



Product Description

AFT 118-896 MHz, UNITY GAIN, 1/4 WAVE, MOBILE, N/A CONNECTOR

Technical Specifications

alpha frequency	Mid Band	VHF	220 BAND	UHF	700 Band	800 Band	Cellular
cable	N/A	N/A	N/A	N/A	N/A	N/A	N/A
mount type	A-base	A-base	A-base	A-base	A-base	A-base	A-base
maximum power (W)	200W	200W	200W	200W	200W	200W	200W
connector	N/A	N/A	N/A	N/A	N/A	N/A	N/A
base load (Y/N)	N	N	N	N	N	N	N

gain	unity	unity	unity	unity	unity	unity	unity
frequency (bandwidth)	118-896 MHz	118-896 MHz	118-896 MHz	118-896 MHz	118-896 MHz	118-896 MHz	118-896 MHz
VSWR	<1.5:1	<1.5:1	<1.5:1	<1.5:1	<1.5:1	<1.5:1	<1.5:1
wavelength	1/4	1/4	1/4	1/4	1/4	1/4	1/4
whip length							
whip material	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel
Weight	1.53 LB						
Warranty	1 year						
Shipping *	Parcel Freight						