



Smart Technology. Delivered.

SPRING B4303S

Mobile Load Coil Antenna



PREMIUM MOBILE LOAD COIL ANTENNAS ARE INDUSTRY STANDARD

Laird's ongoing commitment to refinement in mechanical and electrical design results in the most technically-advanced mobile load coil antennas on the market. Exclusive features such as stainless steel whips, housings constructed with ABS material injection molded around a solid brass insert, and gold plated push pin contacts make Laird the obvious choice for quality and long lasting value for demanding mobile radio communications.


FEATURES

- Easily-removable rod allows the mount to stay water tight during car washes
- O-ring built into the base creates a weather-tight seal
- ABS material is injection-molded directly around the solid brass inserts for a virtually indestructible housing that does not leak or disassemble
- All silver soldered joints provide an electrically and mechanically secure connection

MARKETS

- Public safety
- Transportation
- Utility
- Military mobile

ANTENNA PATTERNS



Normalized to 3 dBi
Elevation Pattern (Y, Z, or H-plane)

Americas: +1.847.839.6925
IAS-AmericasSales@lairdtech.com

Europe: +44.1628.858941
IAS-EUSales@lairdtech.com

Asia:
IAS-AsiaSales@lairdtech.com

Middle East and Africa: +44.1628.858941
IAS-MEASales@lairdtech.com

www.lairdtech.com



Smart Technology. Delivered.

SPRING B4303S

Mobile Load Coil Antenna

SPECIFICATIONS	
Frequency Range	430-450 MHz
VSWR	<2.1
Nominal Gain	3 dBi
Maximum Power	200 W
Nominal Impedance	50 Ω
Polarization	Vertical
Pattern	Omnidirectional
Half-Power Beamwidth (Elevation ° x Azimuth °)	70 ° x 360 °
Coaxial Cable Length and Type (for Vertical Polarization)	None
Terminations	NMO
Noise Suppressor	BlackHawk NS1535 1-35 Volt, 15 Amp Noise Suppressor (sold separately)
Height	19 3/8" (See cutting chart)
Diameter	1.44"
Weight	<0.5 lb
Equivalent Flat Plane Area (wind resistance in square feet)	0.023 sq. ft.
Mounting Information (sold separately)	NMO mountable
Material Substance Compliance	RoHS

MODEL AND ORDERING INFORMATION

MODEL	DESCRIPTION	HEIGHT	TUNING
B4303S	430-450 MHz, 5/8 wave, chrome finish	23"	See Cutting Chart
BB4303S	430-450 MHz, 5/8 Wave, black finish	23"	See Cutting Chart

B4303S CUTTING CHART

FREQUENCY	WHIP LENGTH
430 MHz	9 13/16"
435 MHz	9 5/8"
440 MHz	18 5/16"
445 MHz	9"
450 MHz	8 3/4"

ANT-DS-B4303S 1017

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any Laird materials or products for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2017 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.