



2.5 GHZ WIDE BAND PANEL ANTENNA

Laird Technologies' S25015PT is a directional panel antenna for use in WiMax, WLAN and WISP applications. Enclosed in a low-profile radome, the antenna is mounted using the included tilt mast mount. The antenna element is connected to the communication hardware via a low loss, plenum-rated, coax pigtail. The radiation patterns are uniform and symmetrical, providing high-level signal density into defined coverage zones. This antenna will greatly enhance the performance of wireless systems.

FEATURES

- Low profile housing
- IP66 Rating
- Heavy Duty Tilt Mount
- Performance optimized using Laird Technologies' proprietary RF optimization tools
- Various connector and coax lengths options available

MARKETS

- WiMax networks
- WISP networks
- WLAN networks
- Designed specifically to support 802.11,b/g networks
- Campus
- Public safety wireless systems

SPECIFICATIONS

PARAMETER	SPECIFICATIONS
Part Number	S25015PT
Frequency	2400-2700 MHz
Gain	14 dBi @ 2450 MHz 15 dBi @ 2600 MHz
3 dB Beamwidth-Azimuth	25°
3 dB Beamwidth-Elevation	25°
Polarization:	Linear, Vertical / Horizontal
VSWR	2.0:1
Cable Length in. (cm)	39" (100) RG 58 rated (other lengths available)
RF Connector	N (male)
Power Rating	1 W (average) /10 W (peak)
Radome	Polycarbonate
Dimensions (mm)	10.2" x 10.2" x 1.3" (259.1 x 259.1 x 33.5)
Weight	907.2g
Wind Surface Area	@ 0°, 0.067m ² / @ 90°, 0.009m ²
Wind Survival	200 km/h
Operational Temperature	-40°C to +75°C
Mount Style	Tilt for Mast
Water / Dust Seal Rating	IP-66
RoHS	Compliant

global solutions: local support.™


Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com


Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

Antenna Patterns



2.6 GHz H Plane



2.6 GHz E Plane

SYSTEM ORDERING INFORMATION

- S25015PT 2400-2700 MHz 14 dBi panel antenna
- S25015PT39NM 2400-2700 MHz 14 dBi panel antenna with N Male connector
- S25015PT39SMM 2400-2700 MHz 14 dBi panel antenna with SMA Male connector

ANT-DS-S25015PT 1110

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2010 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trade marks or registered trade marks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.