

TINA-D

~16° diffused spot beam optimized for CREE XP-E

TECHNICAL SPECIFICATIONS:

Dimensions

Height

Fastening

9

ta

ROHS compliant yes (1)

9.7 mm tape

Ø 16.1 mm



PRODUCT DATASHEET

FA10644_TINA-D

MATERIAL SPECIFICATIONS:


Component	Туре	Material	Colour	Finish
TINA-D	Single lens	PMMA	clear	
TINA-XP-H-TAPE-WHT	Holder	PC	white	
TINA-TAPE3	Tape	PU tape	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FA10644_TINA-D	Single lens	2016	288	144	4.2
» Box size: 470 x 240 x 105 mm					



PRODUCT DATASHEET FA10644_TINA-D



LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.





PHOTOMETRIC DATA (MEASURED):

CREE \$	•		
LED	™ XP-E		
FWHM	14.0°		
	93 %		
Efficiency			
Peak intensity	9.6 cd/lm		
LEDs/each optic			
Light colour	White		
Required compor	ients.		
CREE \$	TW		
LED	XP-G		
FWHM	20.0°		
Efficiency	93 %		
Peak intensity	5.1 cd/lm		
LEDs/each optic			
Light colour	White		
Required compor			
CREE LED FWHM Efficiency Peak intensity LEDs/each optic Light colour Required compor	XT-E 17.0° 94 % 6.2 cd/lm 1 White		9°
SEOUL SEMICONDUCTOR			0 ⁴ 155
LED	Z5		
FWHM	12.0°		
Efficiency	%		
LEDs/each optic			
Light colour	White		
Required compor			
compo			



PRODUCT DATASHEET FA10644_TINA-D

PHOTOMETRIC DATA (MEASURED):

SEOUL SEMICONDUCTOR LED FWHM Efficiency Peak intensity LEDs/each optic Light colour	Z5M1/Z5M2 16.0° 94 % 7.4 cd/lm 1 White	5° 600 6°
Required compor	ients:	35° 80° 35° 36°
TOSHIBA Leading Innovation >>> LED FWHM Efficiency Peak intensity LEDs/each optic Light colour Required compor	White	200 200 200 200 200 200 200 200



PRODUCT DATASHEET FA10644_TINA-D

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Local sales and technical support www.ledil.com/ where_to_buy

Shipping locations Salo, Finland Hong Kong, China

Distribution Partners www.ledil.com/ where_to_buy