



**Sales Outline Drawing**Revision **B**

**May not be suitable for all medical and aerospace applications.**  
**Specifications: Contact Mallory Sonalert to discuss your application.**

|  |                                   |
|--|-----------------------------------|
| Oscillation Frequency (Hz)                           | 2731                              |
| Operating Voltage (Vp-p)                             | 2 ~ 4                             |
| Rated Voltage (Vp-p)                                 | 3                                 |
| Current Consumption Max. (mA)                        | 80 at Rated Voltage               |
| Sound Pressure Level (dB/min)                        | 85 at 10cm at Rated Voltage       |
| Coil Resistance ( $\Omega$ )                         | $16 \pm 3$                        |
| Operating Temperature ( $^{\circ}\text{C}$ )         | $-20 \sim +70$                    |
| Storage Temperature ( $^{\circ}\text{C}$ )           | $-30 \sim +80$                    |
| Type of Connection Terminal                          | SMD                               |
| Housing  | LCP plastic resin (Color : Black) |
| Weight (Grams)                                       | 0.8                               |
| Condition by reflow soldering ( $^{\circ}\text{C}$ ) | $250 \pm 5$ / within 10 sec       |
| Condition by hand soldering ( $^{\circ}\text{C}$ )   | $350 \pm 20$ / within 5 sec       |
| Options  | For other options contact factory |

**Dimensions:** (units: mm)**RoHS Compliant****Packaging:**

Parts are supplied on tape-and-reel, 1000 pcs per reel.



1 Reel : 1000PCS