

4140A Liquid



Flux Remover for PC Boards

4140A cleans post solder residues quickly and conveniently. Its plastic safe formula removes rosin, non-rosin, and no clean fluxes, as well as both ionic and non-ionic residues.

This product is used for spot cleaning flux while repairing or prototyping electronic circuits.

Read the product SDS before using this product (downloadable at www.mgchemicals.com).



Features and Benefits

- Safe on most plastics
- Moderate dry time
- Zero residue

Available Packaging

Cat. No.	Packaging	Net Vol.	Net Wt.
4140A-945ML	Bottle	945 mL	719 g
4140A-945MLCA	Bottle	945 mL	719 g
4140A-3.78L	Jug	3.78 L	2.87 kg

Contact Information

MG Chemicals, 1210 Corporate Drive
Burlington, Ontario, Canada L7L 5R6

Email: support@mgchemicals.com

Phone: North America: +(1)800-340-0772

International: +(1) 905-331-1396

Europe: +(44)1663 362888

Properties

Viscosity @ 25 °C	<20.5 mm ² /s
Density	0.76 g/mL
Shelf Life	5 y
Calculated VOC	735 g/L
Flash Point	-4 °C
Boiling Point	>83 °C
Auto-ignition Temperature	285 °C
Water Miscibility	Partially miscible

Storage and Handling

Store between -20 and 40 °C in a in a dry area, away from sunlight (see SDS).

Disclaimer

This information is believed to be accurate. It is intended for professional end-users who have the skills required to evaluate and use the data properly. M.G. Chemicals Ltd. does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.