

Material Safety Data Sheet

Revision Date February 4th, 2005 Head Office **Prepared by** David MacKinnon Technical Information 1-800-201-8822 or support@mgchemicals.com Emergency Phone Canutech (613) 996-6666 Collect 24 hrs

9347 - 193 Street, Surrey, B.C., V4N 4E7

For updates please download from <u>www.mgchemicals.com</u> or fax requests to 1-800-708-9888

Section 1: Product Identification

MSDS Code: 4190-GP

Name: Green Overcoat Pen

Related Part Numbers: 4190-GP

Use: Protective coating for pc boards.

Section 2: Hazardous Ingredients					
Section 2: Hazal yous thui equents	Santian	.	Lazardauc	L D G F O G	ionte
	Section	2:	Hazal uous	Indred	ients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
108-88-3	toluene	15 – 40	50ppm	100ppm	150ppm
64-17-5	ethyle alcohol	7 – 13	200ppm	200ppm	250ppm
110-43-0	2-heptanone	7 – 13	50 ppm	100ppm	n/e
110-19-0	2-methylpropyl ester acetic acid	7 – 13	150ppm	150ppm	n/e
123-86-4	n-butyl acetate	7 – 13	150ppm	150ppm	200ppm
141-78-6	ethyl acetate	1 – 5	400ppm	400ppm	n/e
67-63-0	2-propanol	0.1 – 1	400ppm	400ppm	500ppm

Section 3: Hazards Identification

WHMIS Codes:	B2, D24	4					
NFPA Ratings:	Health	1	Flammability	3	Reactivity	0	
HMIS Ratings:	Health	1	Flammability	3	Reactivity	0	
Eyes:	Causes	eye	e irritation, includ	ding i	redness, swe	elling, pain, tearing, and hazy vision.	
Skin:	Causes	Causes skin irritation, including redness, swelling, dryness, and itching.					
Inhalation:	May cause irritation of the nose and throat.						
Ingestion:	Ingestion is not a like route of exposure to this product.						
Chronic:	Prolong	ed	exposure may ca	use	liver and kid	Iney damage.	

Section 4: First Aid Measure

Eyes:	Remove contact lenses. Flush with water or saline for 20 minutes. Get medical aid.
Skin:	Wash skin with large quantities of soap and water. Get medical aid if symptoms persist.
Inhalation:	Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.
Ingestion:	Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical aid.

Section 5: Fire Fighting Measures

Autoignition Temperature:	465°C	Flash Point: -18°C	LEL / UEL: 1 / 36
Extinguishing Media:	Use water spray, dry	chemical, carbon dioxide, or chemic	al foam.



General Information:

Will burn if involved in a fire. Flash back along vapor trail is possible.

Section 6: Accidental Release Measures

SpillRemove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection.Procedure:Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further
residue with paper towel and place in container. Wash spill area with soap and water.

Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do not expose container to heat or flame.

Storage: Keep away from sources of ignition. Store in a cool, dry, well ventilated area, away from incompatible substances. Keep from freezing.

Section 8: Exposure Controls

Routes of entry:Eyes, ingestion, inhalation, and skin.Ventilation:Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure
limits.Personal
Protection:Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective
clothing to prevent skin contact. Use a NIOSH approved respirator when necessary.

Section 9: Physical and Chemical Properties

Physical State:	Liquid	Odor:	ethereal	Solubility:	partial	Evaporation Rate:	fast		
Boiling Point:	59°C	Specific Gravity:		Vapor Pressure:	1PSI @21°C	Vapor Density:		pH:	7

Section 10: Stability and Reactivity

Stability:	Stable at normal temperatures and pressures.
Conditions to avoid:	Temperatures over 40°C, ignition sources, and incompatible substances.
Incompatibilities:	Alkali and alkaline earth metals, powdered aluminum, zinc, magnesium, and beryllium, lithium aluminum hydride, potassium tert-butoxide, nitrates, strong acids, strong oxidizers, chlorosulphonic acid, hydrogen peroxide.
Polymerization:	Will not occur.
Decomposition:	Carbon monoxide, carbon dioxide, nitrogen oxides



Section 11: Toxicological Information

Sensitization: (effects of repeated exposure)	Prolonged or repeated skin contact may cause dermatitis.			
Carcinogenicity: (risk of cancer)	No			
Teratogenicity: (risk of malformation in an unborn fetus)	No			
Reproductive Toxicity: (risk of sterility)	This product contains xylene and toluene, both chemicals known to cause reproductive toxicity.			
Mutangenicity: (risk of heritable genetic effects)	No			
Lethal Exposure Ingestion (LD50) Concentrations:): 7400 Inhalation 16000 Skin n/e mg/kg (rat) (LC50): ppm/4h (rat) (LD50):			

Section 12: I	Ecological Inf	ormation			
General Information:	Avoid runoff int environmental	o storms and sewers whic damage.	ch lead into waterways	. Water runoff can	i cause
Environmental I	mpact Data: (perce	ntage by weight)			
CFC: 0	HFC:	Cl.Solv.: 0	VOC: 53	HCFC: 0	ODP : 0

Section 13: Disposal Information

GeneralDispose of in accordance with all local, provincial, state, and federal regulations. Water runoffInformation:can cause environmental damage.

Section 14: Transportation Information

Ground:

Non-regulated, ORM-D

Air:

Shipper must be trained and certified. Refer to IATA regulations.

Sea:

Shipper must be trained and certified. Refer to IMDG regulations.

Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations. SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

None of the chemicals in this product have a reportable quantity.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product contains the following chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372: Methanol (CAS #67-56-1, <1% by weight).

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depletors.

This product does not contain any class 2 ozone depletors.

This product contains methanol (CAS #67-56-1, 2% by weight), listed as a hazardous air pollutant.

Section 15: Regulatory Information Cont.



This product contains toluene, listed under chemicals know to the state to cause reproductive toxicity.

Health Canada

Labeling and containers used in this product are listed in compliance with Consumer Chemicals and Container regulations.

Environment Canada

Chemicals in this product are listed on the Domestic Substances List in the Canadian Environmental Protection Act

This product does not contain any ozone depleting substances.

Industry and Science Canada

Labeling, product identity, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance with the Consumer Packaging and Labeling Act and Regulations. This product is not slack filled in accordance to chapter 4 prohibitions.

RoHS (The restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2004).

This product is RoHS compliant.

Section 16: Other Information

Definitions: n/a = not applicable, n/e = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in accordance with federal, state, and local regulations.