



Micro Commercial Components



Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

1N4150

Features

- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)
- Low Current Leakage
- Compression Bond Construction
- Low Cost
- Marking : Cathode band and type number
- Moisture Sensitivity Level 1

Maximum Ratings

- Operating Temperature: -55°C to +150°C
- Storage Temperature: -55°C to +150°C
- Maximum Thermal Resistance; 300°C/W Junction To Ambient


Electrical Characteristics @ 25°C Unless Otherwise Specified

Reverse Voltage	V_R	50V	
Breakdown Voltage	B_V	75V	$I_R=5.0 \mu A$
Average Rectified Current	I_O	200mA	
Power Dissipation	P_{TOT}	500mW	
Peak Forward Surge Current	I_{FSM}	1.0A 4.0A	Pulse Width=1.0S Pulse Width=1.0μS
Maximum Instantaneous Forward Voltage	V_F	1.0V	$I_{FM} = 100mA;$ $T_J = 25°C^*$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	100nA 100μA	$V_R=50Volts$ $T_J = 25°C$ $T_J = 150°C$
Maximum Junction Capacitance	C_J	2.5pF	Measured at 1.0MHz, $V_R=0$
Maximum Reverse Recovery Time	T_{rr}	4.0nS	$I_F=10mA$ $V_R=6.0V$ $R_L=100\Omega$

Note: 1. Lead in Glass Exemption Applied, see EU Directive Annex 7(C)-I.

500mW 75 Volt Silicon Epitaxial Diode

DO-35



DIMENSIONS

DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.166	---	4.2	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.000	---	25.40	---	

Electrical characteristic curves




Fig. 1 Forward characteristics




Fig. 2 Reverse characteristics



Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel: 10Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/AmmoBox
Part Number-BP	Bulk: 100Kpcs/Carton

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

www.mccsemi.com